


Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of the utility model or design.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.



|   |                                               |                          |                                                            |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|---|-----------------------------------------------|--------------------------|------------------------------------------------------------|------|-----------------|-------------------|--------------------|------|-------------------|------|-----------------|-------------------------------|----------------|------|
|   | Number of contacts                            | Standard                 | 3                                                          | 4    | 5               | 5                 | 6                  | 7    | 7                 | 8    | 12              | 14                            | 14             | 19   |
|   | Contact arrangement                           | IEC 61076-2-106          | 03-a                                                       | 04-a | 05-a            | 05-b              | 06-a               | 07-a | 07-b              | 08-a | 12-a            | 14-a                          | 14-b           | 19-a |
|   | Contact arrangement                           | IEC 60130-9 <sup>n</sup> | yes                                                        |      | no              | yes               |                    | no   | yes               |      | no              |                               |                |      |
|   | Rated voltage <sup>2)</sup>                   | IEC 60664-1              | 300 V<br>(100 V)                                           |      | 300 V<br>(63 V) | 100 V<br>(32 V)   | 300 V<br>(63 V)    |      | 100 V<br>(32 V)   |      | 150 V<br>(32 V) |                               | 60 V<br>(32 V) |      |
|   | Rated voltage                                 | UL 1977                  | 250V                                                       |      |                 |                   |                    |      |                   |      | 60V             |                               |                |      |
|   | Rated impulse withstand voltage <sup>2)</sup> | IEC 60664-1              | 1500 V<br>(1500 V)                                         |      |                 | 1200 V<br>(800 V) | 1500 V<br>(1500 V) |      | 1200 V<br>(800 V) |      |                 |                               |                |      |
|   | Pollution degree <sup>2)</sup>                | IEC 60664-1              | 1 (2)                                                      |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
| C | Installation category                         | IEC 60664-1              | I                                                          |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | Insulation group                              | IEC 60664-1              | II, 400 ≤ CTI < 600                                        |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | Current rating                                | IEC 60512-5-2<br>UL 1977 | 10A/+40°C                                                  |      | 7A/+40°C        |                   |                    |      |                   |      | 3A/+40°C        |                               |                |      |
|   | Insulation resistance                         | IEC 60512-3-1            | >10 <sup>10</sup> Ohm <sup>3)</sup>                        |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | Contact resistance                            | IEC 60512-2-1            | <5mOhm                                                     |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | Climatic category                             | IEC 60668-1              | 40 / 100 / 56                                              |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | Temperatur range                              | IEC 60668-1              | -40°C...+100°C / -40°F...+212°F                            |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | IP degree                                     | TEC 60529                | IP 40                                                      |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
| B | Insertion and withdrawal force                | IEC 60512-13-2           | 25N                                                        | 30N  | 35N             | 35N               | 50N                | 55N  | 55N               | 60N  | 50N             | 50N                           | 50N            | 60N  |
|   | mechanical operation                          | IEC 60512-9-1            | Silver ≥500 mating cycles / Gold ≥1000 mating cycles       |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | housing material                              |                          | brass and / or zinc die cast, nickel plated or thermoplast |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | dielectric material                           |                          | thermoplastic                                              |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | contacts                                      |                          | silver or gold plated                                      |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | termination technique                         |                          | solder                                                     |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | wire gauge                                    |                          | ≤0,5mm <sup>2</sup> / 20 AWG                               |      |                 |                   |                    |      |                   |      |                 | ≤0,35mm <sup>2</sup> / 22 AWG |                |      |
|   | flamability                                   |                          | UL 94 V0                                                   |      |                 |                   |                    |      |                   |      |                 |                               |                |      |
|   | locking system                                |                          | metal screw coupling; tightening torque 0,7 - 1,5 Nm       |      |                 |                   |                    |      |                   |      |                 |                               |                |      |

<sup>1)</sup> Edition 2000-05  
<sup>2)</sup> values in brackets are according to DIN EN 61076-2-106  
<sup>3)</sup> under operating conditions >10<sup>8</sup> Ohm

Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.

Remark for gold plated contacts:  
In order to avoid brittle inter-metallic connections, gold plated terminals have to be tin-plated in the solder area.

All technical data have been measured in a laboratory environment and can be different during practical usage of the product. Any product information is for descriptive usage only and not legally binding; particularly the information does not constitute or provide any legal guaranties ("Beschaffenheitsgarantie" or "Haltbarkeitsgarantie").

|                                            |                                                                        |                 |              |
|--------------------------------------------|------------------------------------------------------------------------|-----------------|--------------|
|                                            | 19<br>(19-a)                                                           | Ag              | T 3691 004 U |
|                                            | 14<br>(14-b)                                                           | Ag              | T 3671 004 U |
|                                            | 14<br>(14-a)                                                           | Ag              | T 3651 044 U |
|                                            | 12<br>(12-a)                                                           | Ag              | T 3636 044 U |
|                                            | 8<br>(08-a)                                                            | Ag              | T 3505 004 U |
|                                            | 7<br>(07-b)                                                            | Ag              | T 3485 004 U |
|                                            | 7<br>(07-a)                                                            | Ag              | T 3476 004 U |
|                                            | 6<br>(6-a)                                                             | Ag              | T 3401 004 U |
|                                            | 5<br>(05-b)                                                            | Ag              | T 3361 004 U |
|                                            | 5<br>(05-a)                                                            | Ag              | T 3361 048 U |
|                                            | 4<br>(04-a)                                                            | Ag              | T 3301 004 U |
|                                            | 3<br>(03-a)                                                            | Ag              | T 3261 004 U |
|                                            | 2<br>(Pin 1+3)                                                         | Ag              | T 3201 004 U |
|                                            | 2<br>(Pin 1+3)                                                         | Au              | T 3201 048 U |
| Contact arrangement<br>View on mating side | Number of contacts<br>(Contact arrangement acc.<br>DIN EN 61076-2-106) | contact plating | Part number  |

|                                         |                      |            |        |                                 |            |                                                                                       |  |                  |  |                                                                                       |  |
|-----------------------------------------|----------------------|------------|--------|---------------------------------|------------|---------------------------------------------------------------------------------------|--|------------------|--|---------------------------------------------------------------------------------------|--|
| Gewicht (errechnet) / Calc WT : 34,46 g |                      |            |        | Zul. Abw./Tolerances :          |            | Maßstab / Scale : 2:1                                                                 |  | A3               |  |  |  |
| Prüfmaß / Testdimension                 |                      |            |        | ISO 2768-c                      |            |  |  | CUSTOMER DRAWING |  |                                                                                       |  |
| Teileindex / Partindexnumber:           |                      |            |        |                                 |            |                                                                                       |  |                  |  |                                                                                       |  |
| Bagatelle change: 23.02.2021 MCARLE     |                      |            |        |                                 |            |                                                                                       |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Gez.                            | 30.11.2020 | Female cable connector<br>PG7, cable diameter 4-6mm                                   |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Drawn                           | MCARLE     |                                                                                       |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Status                          | Released   |                                                                                       |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Gepr.                           | 10.02.2021 |                                                                                       |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Checked                         | MBERTSCH   |                                                                                       |  |                  |  |                                                                                       |  |
|                                         |                      |            |        | Amphenol Tuchel Industrial GmbH |            | M DA T 3XXX 004+048 U                                                                 |  |                  |  | Blatt/Sheet<br>1                                                                      |  |
| 02                                      | 202000083            | 05.02.2021 | MCARLE |                                 |            |                                                                                       |  |                  |  | 1 Bl.                                                                                 |  |
| Index                                   | Änderung/Description | Datum/Date | Name   |                                 |            | Ers. f. / Replacement for : M-DA T 3XXX 004+048 U Rev01                               |  |                  |  |                                                                                       |  |