




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **8**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Connector Contact Load Condition	Selectively Loaded
PCB Mount Orientation	Vertical
Number of Positions	8
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

--	--



Primary Product Color	Natural
-----------------------	---------

Contact Features

	39.7 µin
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	.8 µm[31.49 – 70.86 µin]
PCB Contact Termination Area Plating Material Finish	Matte
Mating Square Post Dimension	1.14 mm[.045 in]
Contact Shape & Form	Square
Contact Layout	Inline
Contact Mating Area Length	7.7 mm[.303 in]
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	1 µm[39.37 µin]
Contact Type	Pin
Contact Current Rating (Max)	8 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Termination Post & Tail Length	3.7 mm[.146 in]
Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
Mating Retention Type	Latch
Mating Alignment Type	Polarization
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Material	Glass-Filled PBT



Dimensions

	1.245 in
Connector Width	8.5 mm[.33 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Connector Height	10.7 mm[.421 in]

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	UL
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


TE Part # 5-1123722-5 3.96 EP PLUG HSG 5P(BLACK)	TE Part # 4-1565036-6 EP CONN.HDR ASSY 6/7POS-W/O NO.2	TE Part # 4-1123722-5 3.96 EP PLUG HSG 5P(RED)	TE Part # 1123721-1 EP CONN. REC CONTACT
TE Part # 6-1565036-6 EP CONN.HDR ASSY 6/7POS-W/O NO.2	TE Part # 1123721-2 ECONOMY POWER CONN REC CONT	TE Part # 7-1565036-4 EP CONN.HDR ASSY 4/5POS-W/O NO.4	TE Part # 2-1123722-5 3.96 EP PLUG HSG 5P(YELLOW)
TE Part # 2-1565036-6 EP CONN.HDR ASSY 6/7POS-W/O NO.2	TE Part # 1-1123722-5 3.96 EP PLUG HSG 5P(NATURAL)	TE Part # 5-1565036-4 EP CONN.HDR ASSY 4/5POS-W/O NO.4	TE Part # 3-1123722-5 3.96 EP PLUG HSG 5P(BLUE)
TE Part # 6-1123722-5 3.96 EP PLUG HSG 5P(GREEN)	TE Part # 3-1565036-6 EP CONN.HDR ASSY 6/7POS-W/O NO.2	TE Part # 1744497-8 08P EP-II HOUSING, GREY	TE Part # 1744416-8 8 POS EP II HSG, GLOW WIRE



TE Part # 3-1565036-4
EP CONN.HDR ASSY 4/5POS-W/O NO.4



TE Part # 2-1565036-4
EP CONN.HDR ASSY 4/5POS-W/O NO.4



TE Part # 1-1565036-6
EP CONN.HDR ASSY 6/7POS-W/O NO.6



TE Part # 4-1565036-4
EP CONN.HDR ASSY 4/5POS-W/O NO.4

Also in the Series | Economy Power



Connector Contacts(13)



Connector Hardware(2)



Power Contacts(7)



Rectangular Connector Housings(104)



Rectangular Power Connectors(547)



Standard Rectangular Connectors(104)



Wire-to-Board Connector Assemblies & Housings(104)


Customers Also Bought




TE Part #YD369-B99-NS400000
369 9 WAY PANEL MNT REC, 90 PCB GOLD,SKT



TE Part #YD369-B99-NP400000
369 9 WAY PANEL MNT REC, 90 PCB GOLD,PIN




TE Part #YD369-B99-AP400000
369 9 WAY PANEL MNT REC, 90 PCB GOLD,PIN




TE Part #2-1623795-3
SQP2 R047 5% WIRE



TE Part #1-1630019-4
HSC200 2K4 5%



TE Part #1-1969694-4
PTL 1X4 PCB HEADER R/A HITEMP KEY A LGR



TE Part #9-2176397-4
3502 7K5 1%



TE Part #YDTS24T21-35SNV001
RECP ASSY



Documents

Product Drawings

EP CONN HDR ASSY 5/8P SPECIAL

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1565036-5_AD_c-1-1565036-5-ad.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1565036-5_AD_c-1-1565036-5-ad.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1565036-5_AD_c-1-1565036-5-ad.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

7-1773458-5_ECONOMY_POWER_QRG

English

Product Specifications

Application Specification

Japanese

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Economy Power (EP) Connector

Japanese

Agency Approvals

UL Report

1-1565036-5

PCB Mount Header, Vertical, Wire-to-Board, 8 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin (Sn), Economy Power



English