




Automotive Parts > Automotive Connectors > Automotive Housings



Nominal Voltage Architecture: 12 V, 24 V, 48 V

Connector & Housing Type: Housing for Female Terminals

Number of Positions: 5

Sealable: Yes

Operating Temperature Range: -40 – 130 °C [-40 – 266 °F]

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	5
Number of Rows	1

Electrical Characteristics

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V, 24 V, 48 V

Body Features



Cable Exit Angle	180 °
Primary Product Color	Black
Connector & Keying Code	A

Contact Features

Contact Size	1.2mm
Contact Type	Receptacle
Mating Tab Width	1.2 mm[.047 in]
Contact Current Rating (Max)	25 A

Mechanical Attachment

Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Product Width	26.5 mm[1.043 in]
Product Length	28.7 mm[1.13 in]
Connector Height	16.5 mm[.65 in]

Usage Conditions

Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]
Operating Temperature (Max)	125 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

IP Rating	IP6K9K
-----------	--------

Packaging Features

Packaging Method	Box
Packaging Quantity	1000



Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts




TE Part # 5-1579007-3
EXTRACTION TOOL



TE Part # 967067-2
MQS EINZELLEITDICHT



TE Part # 967067-1
MQS SGL WIRE SEAL




TE Part # CAT-N14-RC4812
48V Ready 1.2mm Sealed Connectors





TE Part # 2-2236954-5
5POS, MCON 1.2 LL TAB SEALED
COD B



TE Part # 1-2141520-4
5POS, MCON 1.2 LL TAB SEALED
COD A



TE Part # CAT-N13-MSLLT12
MCON 1.2 48V Locking Lance
Receptacle and Tab Terminals

Also in the Series | MCON 1.2mm



Automotive Connector Locks & Position Assurance(9)



Automotive Housings(354)



Automotive Seals & Cavity Plugs(16)




Automotive Signal & Power Connector Housings(350)



Other Automotive Connector Accessories(12)

Customers Also Bought



TE Part #40577
SPADE TERMINAL 18-14 AWG BR



TE Part #41274-1
250 FASTON,REC.,18-14 AWG,TPBR



TE Part #5-102203-4
07 MODII HDR SRR SHRDLF



TE Part #640551-2
02P MTA156 COVER



TE Part #5-1676123-9
1/2W SM M/OX 5% 220R



TE Part #1-2141520-1
5POS, MCON 1.2 LL TAB SEALED
COD A



TE Part #2174803-2
PUSH-PUSH MICRO SIM
CONNECTOR



TE Part #2405028-1
26POS, HYBRID, PIN HSG ASSY, SLD,
COD A



Documents

Product Drawings

5POS, MCON 1.2 LL REC SEALED

English

5POS, MCON 1.2 LL REC SEALED

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-1670921-1_E.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1670921-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1670921-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English