



Automotive Parts > Automotive Connectors > Automotive Housings > Timer Connector Housing



Nominal Voltage Architecture: 12 V, 24 V, 48 V

Connector & Housing Type: Housing for Female Terminals

Number of Positions: 2

Sealable: Yes

Operating Temperature Range: -40 – 120 °C [-40 – 248 °F]

[All Timer Connector Housing \(436\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2
Number of Rows	1

Electrical Characteristics

Nominal Voltage Architecture	12 V, 24 V, 48 V
------------------------------	------------------



Body Features

Cable Exit Angle	180 °
Primary Product Color	Black
Connector & Keying Code	B

Contact Features

Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	30 A

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	6.1 mm[.24 in]

Dimensions

Product Width	31 mm[1.22 in]
Product Length	31 mm[1.22 in]
Connector Height	10.3 mm[.78 in]

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature (Max)	120 °C[248 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Packaging Features

Packaging Quantity	900
Packaging Method	Bag



Other

Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-1355664-2 2POS JPT SOCKET HOUSING SWS	TE Part # CAT-T4827-T273 TIMER, RECEPTACLE AND TAB	TE Part # 1355667-1 DICHTUNG F.2P BU-GH
---	--	---



Also in the Series | Junior Power Timer

Automotive Connector Caps & Covers
(12)

Automotive Housings(279)

Automotive Seals & Cavity Plugs(8)

Automotive Terminals(150)

Module Components(1)

Special Purpose Terminals(2)

Customers Also Bought

TE Part #CAT-HST-VERSAFLEX
VERSAFLEX Heat Shrink Tubing

TE Part #HD36-18-8SE
PLG, 8P, AL, E, 12, S

TE Part #180422-2
FF 312 REC 1-2.5MM2 TPBR LP

TE Part #794911-1
6 POS UMNL CIR PLUG HSG

TE Part #794953-8
8P PM PLUG VAL-U-LOK V2

TE Part #1-794953-0
10P PM PLUG VAL-U-LOK V2

TE Part #925176
3P FF 312 HOUSING RECEPTACLE
PA66 CLEAR

TE Part #CAT-T4827-CH8172
Timer Connector Housing

Documents

Product Drawings
JPT EDS BUGH,ASSY2P

English

CAD Files
Customer View Model
ENG_CVM_2-1355668-2_B1.3d_igs.zip



English

Customer View Model

[ENG_CVM_2-1355668-2_B1.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_2-1355668-2_B1.2d_dxf.zip](#)

English

[3D PDF](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Product Specification](#)

English