




Automotive Parts > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Nominal Voltage Architecture: 12 V

Connector & Housing Type: **Housing for Female Terminals**

Number of Positions: 2

Sealable: **Yes**

Operating Temperature Range: -40 – 130 °C [-40 – 266 °F]

[All MQS, CONNECTOR HOUSING \(156\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Board, Wire-to-Device, Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2
Number of Rows	1

Electrical Characteristics

Nominal Voltage Architecture	12 V
------------------------------	------



Body Features

Cable Exit Angle	180 °
Primary Product Color	Gray
Connector & Keying Code	B

Contact Features

Contact Size	.5mm
Contact Type	Receptacle
Mating Tab Width	.5 mm[.019 in]
Contact Current Rating (Max)	3 A

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	Yes
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF15
Centerline (Pitch)	1.8 mm[.07 in]

Dimensions

Product Width	22.05 mm[.868 in]
Product Length	7.6 mm[.299 in]
Connector Height	8.2 mm[.323 in]

Usage Conditions

Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]
Operating Temperature (Max)	130 °C[266 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

IP Rating	IPX9K
UL Flammability Rating	UL 94HB

Packaging Features

--	--



Packaging Method	Box
Packaging Quantity	1000

Other

Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2141464-1
RADIAL SEAL DIA 3.35

TE Part # 2141463-2
2POS,NANOMQS,REC HSG,CODB

TE Part # CAT-M8793-T273
MQS, RECEPTACLE AND TAB

Also in the Series | Nano MQS

Automotive Connector Locks & Position Assurance(3)

Automotive Housings(118)

Automotive Seals & Cavity Plugs(1)

Automotive Signal & Power Connector Housings(118)

Customers Also Bought

TE Part #173645-1
070 TAB CONT 16-20

TE Part #2-1623795-0
SQP10 R22 5% WIRE

TE Part #2-1703930-1
NANOMQS, RECEPTACLE TERMINAL

TE Part #1-2236905-1
NANO TAB 0.5X0.4,TERMINAL

TE Part #CAT-J58-NHFT
NTSEAL Housings Female Terminals

TE Part #CAT-J58-NHMT
NTSEAL Housings Male Terminals

TE Part #2366517-1
FIX RING,CONN KIT

Documents

Product Drawings
2POS,NANOMQS,SOCK HSG,ASSY,SEALED,CODB

English

CAD Files
Customer View Model
ENG_CVM_CVM_2141467-2_B.2d_dxf.zip



English

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_2141467-2_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2141467-2_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

[Application Specification](#)

German

[Application Specification](#)

German

[Application Specification](#)

German