



Automotive Parts > Automotive Connectors > Automotive Headers



PCB Mount Orientation: **Vertical**

Contact Current Rating (Max): **3 A**

Termination Method to PCB: **Surface Mount**

Sealable: **No**

Centerline (Pitch): **1.8 mm [.07 in]**

Features

Product Type Features

Mixed & Hybrid Header	No
Header Type	Fully Shrouded
Connector Shape	Rectangular
Connector Product Type	Connector Assembly
Sealable	No
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	8
Number of Rows	1

Body Features

Connector & Keying Code	A
Primary Product Color	Black



Contact Features

Mating Tab Thickness	.4 mm[.015 in]
Contact Type	Tab
Mating Tab Width	.5 mm[.019 in]
Contact Current Rating (Max)	3 A
Contact Mating Area Plating Material	Tin (Sn)

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mounting Holes	Without
Mating Alignment	With
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	1.8 mm[.07 in]
--------------------	----------------

Dimensions

Connector Width	6.05 mm[.238 in]
Connector Length	20.65 mm[.81 in]

Usage Conditions

Operating Temperature (Max)	130 °C[266 °F]
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

Operation/Application

Solder Process	Reflow Solder Capable
Shielded	No
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94HB
------------------------	---------

Other

Interface Number	114-94000-17, 208-18060
------------------	-------------------------



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


TE Part # 2282267-1
8POS,NANOMQS,REC HSG,CODA

TE Part # 2309873-1
6POS,NANOMQS,REC HSG ASSY, COD A

Also in the Series | [Nano MQS](#)



Automotive Connector Locks & Position Assurance(3)



Automotive Housings(118)



Automotive Seals & Cavity Plugs(1)




Automotive Signal & Power Connector Housings(118)


Customers Also Bought



TE Part #2-338069-0
MICRO-MATCH SMD FTE



TE Part #2311396-2
8POS,TAB0.5X0.4,HDR ASSY,180DEG,COD B



TE Part #2311396-3
8POS,TAB0.5X0.4,HDR ASSY,180DEG,COD C



TE Part #2311714-1
6POS,TAB0.5X0.4,HDR ASSY,90DEG,COD A




TE Part #2314505-1
5POS,TAB0.5X0.4,HDR ASSY,180DEG,COD A



TE Part #2314505-2
5POS,TAB0.5X0.4,HDR ASSY,180DEG,COD B



TE Part #2314513-1
10POS,TAB0.5X0.4,HDR ASSY,180DEG,COD A



TE Part #2317527-1
2X6POS,NANOMQS,HDR ASSY,180DEG,SMD,COD A



TE Part #2317531-1
2X8POS,NANOMQS,HDR ASSY,180DEG,SMD,COD A



TE Part #2410841-1
BLIND PLUG BLOCK ASSAMBLY, FINGER UNLOCK.

Documents

Product Drawings

8POS,TAB0.5X0.4,HDR ASSY,180DEG,COD A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2311396-1_A.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2311396-1_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2311396-1_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Product Specification](#)

English