




Automotive Parts > Automotive Connectors > Automotive Housings > Timer Connector Housing



Nominal Voltage Architecture: 12 V, 24 V

Connector & Housing Type: Housing for Male Terminals

Number of Positions: 18

Sealable: No

Operating Temperature Range: -40 – 120 °C [-40 – 248 °F]

[All Timer Connector Housing \(436\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	18
Number of Rows	3

Electrical Characteristics

Operating Voltage	28 VDC
Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	180 °
Primary Product Color	Natural
Connector & Keying Code	B



Contact Features

Contact Size	2.8mm
Contact Type	Tab
Mating Tab Width	2.8 mm[.11 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	5 mm[.197 in]

Dimensions

Product Width	35.45 mm[1.396 in]
Product Length	37.5 mm[1.476 in]
Connector Height	30.6 mm[1.205 in]

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature (Max)	120 °C[248 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Other

Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-962916-3
TAB 2.8x0.8 CONTACT CF SWS Au



TE Part # CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



TE Part # 7-968974-1
MCP2,8 GEH ASSY 18P

Also in the Series | Timer Connector System



Automotive Connector Caps & Covers (12)




Automotive Housings(186)



Automotive Seals & Cavity Plugs(32)



Automotive Signal & Power Headers(6)



Automotive Terminals(110)



Quick Disconnects(4)

Customers Also Bought



TE Part #SRK-PC-080-25-601
PIN, SOLID, SIZE M8, 25mm2, AG




TE Part #776309-1
CAP HOUSING 2 POSITION




TE Part #776540-1
776310-1 SECONDARY LOCK WITH
120 OHM 1/2



TE Part #CAT-AM705-CH8173
AMP Unsealed Connector Housing



TE Part #4-2213767-3
AV19 DPM 3A MOVE RING LED
WHITE 24V



TE Part #368511-1
070 MLC PLUG 20P HSG

Documents

Product Drawings
TAB HOUSING, 2.8MM, 18POS.

German

CAD Files
Customer View Model
ENG_CVM_CVM_2-967629-1_E.2d_dxf.zip

English

3D PDF

3D

Customer View Model
ENG_CVM_CVM_2-967629-1_E.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_2-967629-1_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



[Product Specifications](#)

[Application Specification](#)

English