



MTA 156

TE Internal #: 3-640433-3


3 Position, Receptacle, Connector Assembly, Insulation

Displacement (IDC), Wire-to-Board, Tin (Sn), UL 94V-2, 3.96 mm [.

156 in] Centerline, MTA 156

[View on TE.com >](#)

Connectors > Rectangular Connectors > Standard Rectangular Connectors



Connector Product Type: **Connector Assembly**

Mating Alignment: **Without**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Contact Mating Area Plating Material: **Tin (Sn)**

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	3
Number of Rows	1
Number of Power Positions	3

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features

Primary Product Color	Red
-----------------------	-----



Cable Exit Angle	90°
------------------	-----

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	30 µm[.762 µin]
Contact Layout	Inline
Contact Base Material	Copper Alloy
Wire Contact Termination Area Plating Thickness	2.03 – 5.08 µm[80 – 200 µin]
Contact Mating Area Plating Material	Tin (Sn)
Contact Retention Within Housing	With
Contact Current Rating (Max)	7 A
Contact Type	Receptacle
Wire Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.03 µm[80 µin]

Termination Features

Termination Method to Wire & Cable	Insulation Displacement (IDC)
------------------------------------	-------------------------------

Mechanical Attachment

Strain Relief	With
Panel Mount Feature	Without
Contact Retention Type Within Housing	Locking Lance
Mating Alignment	Without
Mating Retention	Without
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Wire & Cable IDC Installation Type	Closed End
Centerline (Pitch)	3.96 mm[.156 in]
Housing Material	Nylon

Dimensions

Compatible Insulation Diameter Range	2.41 mm[.095 in]
Connector Height	9.02 mm[.355 in]
Connector Length	11.89 mm[.468 in]
Wire Size	.325 mm²

Usage Conditions



Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
CSA Rating	Certified, LR 7189
UL Flammability Rating	UL 94V-2
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	500
Packaging Method	Bag & Box

Product Compliance

For compliance documentation, visit the product page on TE.com>














EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 640388-3 03P MTA156 HDR ASSY RN STR F/L	 TE Part # 641937-2 03P MTA156 HDR ASSY SQ W/O#3	 TE Part # 644750-3 03P MTA156 HDR ASSY STR RND SN	 TE Part # 644752-3 03P MTA156 HDR ASSY SQ STR F/L
 TE Part # 644753-3 03P MTA156 HDR ASSY RN STR F/L	 TE Part # 58247-1 MTA 156 CRIMP HEAD REPAIR DISCRETE	 TE Part # 2-647123-3 03P MTA156 SHRD HDR ASSY SQ SN	 TE Part # 643071-3 03P MTA156 FD-THRU COVER
 TE Part # 58247-2 MTA 156 CRIMP HEAD PRODUCTION DISCRETE	 TE Part # 3-644611-3 03P MTA156 HDR POL WO PEGS LF	 TE Part # 640384-3 03P MTA156 HDR ASSY STR RND SN	 TE Part # 640387-3 03P MTA156 HDR ASSY SQ R/A
 TE Part # 2472633-1 03P MTA156 HDR ASSY W/O#2 LF W/ CHMFR	 TE Part # 59804-1 MAINTENANCE TOOL	 TE Part # 3-644615-3 03P MTA156 POL HDR ASSY LF	 TE Part # 2-647127-3 03P MTA156 SHRD HDR ASSY LF
 TE Part # 640389-3 03P MTA156 HDR ASSY SQ R/A F/L	 TE Part # 644749-3 03P MTA156 HDR ASSY STR SQ SN	 TE Part # 640385-3 03P MTA156 HDR ASSY SQ R/A	 TE Part # 641937-1 03P MTA156 HDR ASSY STR W/O#2



Also in the Series | **MTA 156**

Connector Caps & Covers(89)	Connector Contacts(4)	Connector Hardware(2)	Insertion & Extraction Tools(1)
PCB Headers & Receptacles(677)	Power Contacts(3)	Rectangular Power Connectors(1178)	Wire-to-Board Headers & Receptacles (677)

Customers Also Bought

TE Part #52924 TERMINAL,PIDG SPR SPD 26-22 6	TE Part #104482-3 08 SHORT PT RCPT HSG DR .100CL	TE Part #163091-8 062 SOC.ASS. TYP3+	TE Part #193846-1 SKT ASSY.
TE Part #320631 TERMINAL,PIDG R 16-14HD 6	TE Part #640251-5 05P SL156 HSG W/O LCK RAMP	TE Part #3-640440-9 09P MTA100 CONN ASSY 22AWG RED	TE Part #3-747579-2 SHLDNG FERRULE, PLTD, BULK PKG
TE Part #1546310-6 6P .563" DR BARRIER STRIP	TE Part #5650868-4 ASSY,RECEPTACLE,EUROCARD,TYPE		



Documents

Product Drawings

03P MTA156 CONN ASSY 22AWG RED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-640433-3_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-640433-3_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-640433-3_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Application Specification

Japanese

Application Specification

English

MTA 156 Ribbon Cable Connector Assemblies (English And Spanish)

English

MTA 156 Ribbon Cable Connector Assemblies (English And Spanish)

Japanese

Agency Approvals

UL

English