



MTA 156

TE Internal #: 3-644615-5
PCB Mount Header, Vertical, Wire-to-Board, 5 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin (Sn), Through Hole - Solder, MTA 156

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**
PCB Mount Orientation: **Vertical**
Connector System: **Wire-to-Board**
Number of Positions: **5**
Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Connector Contact Load Condition	Fully Loaded
Number of Columns	5
Number of Loaded Positions	5
Keying & Polarized Position Locations	None
PCB Mount Orientation	Vertical



Number of Positions	5
Number of Rows	1
Number of Power Positions	5

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Size	1.14mm
Mating Square Post Dimension	1.14 mm[.045 in]
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material Thickness	3.81 – 8.89 µm[150 – 350 µin]
Contact Shape & Form	Square
Contact Layout	Inline
Contact Mating Area Length	11.43 mm[.45 in]
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	3.81 – 8.89 µm[150 – 350 µin]
Contact Type	Tab
Contact Current Rating (Max)	14.24 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
PCB Mount Retention Type	Tab
Mating Retention Type	Polarized Lock



PCB Mount Alignment Type	Pegs
PCB Mount Alignment	With
Mating Retention	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Mating Alignment	Without

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	3.96 mm[.156 in]
Housing Material	Thermoplastic Polyester GF

Dimensions

Connector Width	10.79 mm[.425 in]
Connector Height	13.84 mm[.545 in]
Connector Length	19.69 mm[.775 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 3-640434-5
05P MTA156 CONN ASSY 24AWG WHT

TE Part # 3-640600-5
05P MTA156 CONN ASSY 20AWG LF

TE Part # 3-640433-5
05P MTA156 CONN ASSY 22AWG RED


TE Part # 3-643820-5
05P MTA156 CONN ASSY 24AWG LF

TE Part # 3-643819-5
05P MTA156 CONN ASSY 22AWG RED


TE Part # 3-643818-5
05P MTA156 CONN ASSY 20AWG YEL

TE Part # 3-644466-5
05P MTA156 CONN ASSY 20AWG YEL

TE Part # 3-644468-5
05P MTA156 CONN ASSY 24AWG LF



TE Part # 3-640602-5
05P MTA156 CONN ASSY 24AWG LF




TE Part # 643071-5
05P MTA156 FD-THRU COVER



TE Part # 3-647174-5
05P MTA156 CONN ASSY W/O#4




TE Part # 3-640606-5
05P MTA156 CONN ASSY 22AWG LF



TE Part # 3-640605-5
05P MTA156 CONN ASSY 20AWG LF




TE Part # 3-644462-5
05P MTA156 CONN ASSY 20AWG LF




TE Part # 3-640426-5
05P MTA156 CONN ASSY 18AWG ORA




TE Part # CAT-103156-WBHSM
Receptacle Housing: Wire-to-Board, with Mating Alignment, SL156




TE Part # 3-640430-5
05P MTA156 CONN ASSY 26AWG BLU



TE Part # 3-640601-5
05P MTA156 CONN ASSY 22AWG LF



TE Part # 643067-5
05P MTA156 MOLDED COVER



TE Part # 3-640428-5
05P MTA156 CONN ASSY 22AWG RED


Also in the Series | **MTA 156**



Connector Caps & Covers(89)




Connector Contacts(4)



Connector Hardware(2)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(677)



Power Contacts(3)




Rectangular Power Connectors(1178)



Wire-to-Board Headers & Receptacles (677)


Customers Also Bought




TE Part #4-338309-2
9P.HDP20 PLUG ASSY




TE Part #350787-1
02P UMNL PIN HDR ASSY 94VO



TE Part #641970-1
06P UMNL PIN HDR ASSY 94VO



TE Part #4-1761206-1
4 SDL SE RCPT ASSY PART SIELD



TE Part #1-1903328-4
DYNAMIC 4200S HDR ASSY H 4P X



TE Part #2-2176089-6
RP 1J 0.166W 20K 0.1% 25PPM 1K RL



TE Part #2176232-4
3522 180K 1% 3W



TE Part #5175887-4
CHAMP 050-2 REC ASSY V 26P



TE Part #CAT-025-DRAVS2274
D-Sub Receptacle Assembly: Vertical,
Shell Size 2, 2.74mm

Documents

Product Drawings

05P MTA156 POL HDR ASSY LF

English

CAD Files

Customer View Model

ENG_CVM_3-644615-5_J.2d_dxf.zip

English

3D PDF

English

Customer View Model

ENG_CVM_3-644615-5_J.3d_igs.zip

English

Customer View Model

ENG_CVM_3-644615-5_J.3d_stp.zip

English

3D PDF

3D



Customer View Model

[ENG_CVM_CVM_3-644615-5_E.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-644615-5_E.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_3-644615-5_E.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ENG_DS_82056_MTA_0818.pdf](#)

English

Product Specifications

[Application Specification](#)

English

Agency Approvals

[UL](#)

English