



MTA 156

TE Internal #: 4-644615-6

PCB Mount Header, Vertical, Wire-to-Board, 16 Position, 3.96 mm [.156 in] Centerline, Partially Shrouded, Tin (Sn), Through Hole - Solder, MTA 156

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **16**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Connector Contact Load Condition	Fully Loaded
Number of Columns	16
Number of Loaded Positions	16
Keying & Polarized Position Locations	4&5, 8&9, 12&13
PCB Mount Orientation	Vertical



Number of Positions	16
Number of Rows	1
Number of Power Positions	16

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Size	1.14mm
Mating Square Post Dimension	1.14 mm[.045 in]
Contact Base Material	Copper Alloy
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material Thickness	3.81 – 8.89 µm[150 – 350 µin]
Contact Shape & Form	Square
Contact Layout	Inline
Contact Mating Area Length	11.43 mm[.45 in]
Contact Mating Area Plating Material	Tin (Sn)
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	3.81 – 8.89 µm[150 – 350 µin]
Contact Type	Tab
Contact Current Rating (Max)	14.24 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Square Termination Post & Tail Dimension	1.14 mm[.045 in]
Termination Post & Tail Length	3.18 mm[.125 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
Mating Alignment Type	Backwall Interruptions Between Posts
PCB Mount Retention Type	Tab



Mating Retention Type	Polarized Lock
PCB Mount Alignment Type	Pegs
PCB Mount Alignment	With
Mating Retention	With
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	3.96 mm[.156 in]
Housing Material	Thermoplastic Polyester GF

Dimensions

Connector Width	10.79 mm[.425 in]
Connector Height	13.84 mm[.545 in]
Connector Length	63.27 mm[2.491 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL E28476
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	300
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>




EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 4-640427-6
16P MTA156 CONN ASSY 20AWG YEL



TE Part # 4-640601-6
16P MTA156 CONN ASSY 22AWG LF




TE Part # 4-640602-6
16P MTA156 CONN ASSY 24AWG LF



TE Part # CAT-103156-WBHSM
Receptacle Housing: Wire-to-Board, with Mating Alignment, SL156




TE Part # 1-640551-6
16P MTA156 COVER



TE Part # 1-643071-6
16P MTA156 FD-THRU COVER



TE Part # 4-643817-6
16P MTA156 CONN ASSY 18AWG LF



TE Part # 4-640426-6
16P MTA156 CONN ASSY 18AWG ORA



TE Part # 4-640599-6
16P MTA156 CONN ASSY 18AWG ORA

TE Part # 4-640605-6
16P MTA156 CONN ASSY 20AWG LF

TE Part # 1-640643-6
16P MTA156 COVER F/T

TE Part # 1-643067-6
16P MTA156 MOLDED COVER

TE Part # 4-643819-6
16P MTA156 CONN ASSY 22AWG LF

TE Part # 1-640251-6
16P SL156 HSG W/O LCK RAMP

TE Part # 4-640428-6
16P MTA156 CONN ASSY 22AWG RED

TE Part # 4-640600-6
16P MTA156 CONN ASSY 20AWG LF

Also in the Series | MTA 156

Connector Caps & Covers(89)

Connector Contacts(4)

Connector Hardware(2)

Power Contacts(3)

Rectangular Power Connectors(1178)

Standard Rectangular Connectors(667)

Wire-to-Board Connector Assemblies & Housings(594)

Customers Also Bought

TE Part #1SNK516010R0000
ZS35

TE Part #234832-E
SRCA 2,54 2 M 1 SMD 137 E1 094 *
GURT *

TE Part #244837-E
SMCQ 26 M AB VV 8-13 CL * H007 137
E005

TE Part #254589-E
SMCQ 32 M AB VV 8-13 CL * H007 137
E005



TE Part #5-104666-1
20 SYSTEM 50 HDR DRST SHRD SN

TE Part #966140-3
MESSERLEISTE 12P

TE Part #3-1649328-1
RT334012

TE Part #2-1676481-4
CPF 0603 47R 0.1% 25PPM 1K RL

TE Part #1879229-6
FCR1206 5% 47R

TE Part #5536511-2
2MM FB,ASY,048,SIG,REC,EN,3.55

Documents

Product Drawings

16P MTA156 POL HDR ASSY LF

English

CAD Files

Customer View Model

ENG_CVM_4-644615-6_J.2d_dxf.zip

English

3D PDF

English

Customer View Model

ENG_CVM_4-644615-6_J.3d_igs.zip

English

Customer View Model

ENG_CVM_4-644615-6_J.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_4-644615-6_E.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_4-644615-6_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_4-644615-6_E.3d_stp.zip

English



By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English