



[CONNECTORS](#)

[RF CONNECTORS](#)



✓ Active

TE CONNECTIVITY (TE)

SMA PNL JK DS, 4/FLNG RG402 GS

Subminiature Coax | SMA

1-1478930-0

TE Internal Number: 1-1478930-0

[EU RoHS Compliant with Exemptions](#)

[EU ELV Compliant with Exemptions](#)

Connector Interface SMA

Connector Style Jack

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]

Cable Type RG 402

Sealable No

[↓ PRODUCT DRAWING](#)
English

DOCUMENTATION

Product Drawings

[SMA PANEL JACK 4 HOLE FLANGE DIRECT SOLDER NON CAPTIVE CONTACT RG402/U](#)

PDF (TIFF AVAILABLE)

English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Interface SMA

Connector Style Jack

Sealable No

Body Features

Cable Connector Orientation Straight

Body Material Stainless Steel

Body Plating Material Gold

Contact Features

Center Contact Plating Material Gold

Center Contact Material Beryllium Copper

Connector Product Type Connector Assembly

RF Connector Contact Configuration Not Captivated

Termination Features

Termination Method to Wire & Cable Solder

Mechanical Attachment

Panel Mount Retention Type Flange

Connector Mounting Type Panel

Panel Attachment Style Rear Mount

Dimensions

Mated Outer Diameter (Approximate) 6.35 mm [.25 in]

Panel Cutout 1 x 4.7 + 4 x 2.6

Length 12.7 mm [.5 in]

Usage Conditions

Cable Type RG 402

Packaging Features

Packaging Method Box

Packaging Quantity 100

Other

Dielectric Material PTFE

Flange and Thread Material Stainless Steel

Number of Panel Mounting Holes 4

Grade Professional

PRODUCT COMPLIANCE +

Statement of Compliance

Statement of Compliance

PDF
