



[+ TERMINALS & SPLICES](#)
[RINGS & SPADES](#)



✓ Active

TE CONNECTIVITY (TE)
PIDG SLOTTED TONG
PIDG

130526
TE Internal Number: 130526

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Terminal Type Spade Tongue

Stud Diameter 3.02 mm [.119 in]

Tongue Thickness .78 mm [.032 in]

Wire Size (AWG) 16 – 14

Wire Size (mm²) 1.04 – 2.62

[↓ PRODUCT DRAWING](#)
English

DOCUMENTATION

Product Drawings

TERMINAL, RECTANGULAR TONGUE, P.I.D.G. WIRE SIZE: 16-14 AWG

PDF (TIFF AVAILABLE)

English

Agency Approvals

UL Report

Plastic-Grip, Solistrand, DG, And PIDG Terminals

PDF

English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealable No
Barrel Type Closed Barrel
Wire/Cable Type Regular Wire
Insulated Yes
Insulated Wire Support Yes
Stud Size 4, M2.5
Shape Code SPADE-021
Wire/Cable Composition Stranded

Configuration Features

Terminal Angle Straight

Electrical Characteristics

Voltage (Max) (V) 600

Body Features

Plating Material Tin
Insulation Sleeve Material Copper
Plating Thickness (µm) 2.54
Insulation Support Sleeve Material Copper
Insulation Sleeve Color Blue
Insulation Material Nylon
Inspection Slot No

Contact Features

Terminal Type Spade Tongue
Terminal Orientation Straight

Dimensions

Stud Diameter 3.02 mm [.119 in]
Tongue Thickness .78 mm [.032 in]
Wire Size (AWG) 16 – 14
Wire Size (mm²) 1.04 – 2.62
Wire Insulation Diameter (Max) 3.8 mm [.154 in]
Wire Insulation Diameter 2.7 – 3.8 mm [.106 – .15 in]
Wire Size (CMA) 2050 – 5180
Material Thickness .78 mm [.031 in]
Overall Length 20.65 mm [.813 in]

Usage Conditions

Operating Temperature Range (°C) 150

Operation/Application

Heavy Duty No

Industry Standards

Government Qualified No

Packaging Features

Packaging Method Loose Piece

Packaging Quantity 1000

Other

Barrel Color Blue

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
