


Product: [1308A](#) 



Speaker Cable, 4 Conductor 16 AWG, BC, Unshielded, CM

Product Description

Speaker Cable, CL3 & CM-Rated, 4-16 AWG stranded high conductivity bare copper conductors with polyolefin insulation, PVC jacket with sequential footage marking every two feet

Technical Specifications

Product Overview

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems
------------------------	--

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
16	65x34	High Conductivity Bare Copper	0.058 in	4

Conductor Count:	2
------------------	---

Insulation

Material	Nominal Diameter
PE - Polyethylene	0.083 in

Color Chart

Number	Color
1	Black
2	Red
3	White
4	Green

Outer Shield Material

Material
No Shield

Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.27 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor
19.9 pF/ft

Inductance

Nominal Inductance

0.16 µH/ft

Delay

Nominal Velocity of Propagation (VP) [%]

66 %

Current

Max. Recommended Current [A]

9 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

Operating Temp Range:	-20°C To +75°C
-----------------------	----------------

Mechanical Characteristics

Bulk Cable Weight:	50 lbs/1000ft
Max Recommended Pulling Tension:	130 lbs
Min Bend Radius/Minor Axis:	2.75 in

Standards

NEC/(UL) Specification:	CL3, CM
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1581 Vertical Flame and FT-1 Flame Test
CSA Flammability:	FT1
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6202UE

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
1308A 010U500	Black	UnReel	500 ft	612825111368
1308A 0101000	Black	Reel	1,000 ft	612825111375
1308A 006U500	Blue, Light	UnReel	500 ft	612825111337
1308A 008U500	Gray	UnReel	500 ft	612825111344
1308A 0081000	Gray	Reel	1,000 ft	612825111351

1308A N3UU500	Green, Mil	UnReel	500 ft	612825111320
1308A 1SLU500	White 1SL	UnReel	500 ft	612825111382
1308A 1SL1000	White 1SL	Reel	1,000 ft	612825111399

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

History

Update and Revision:	Revision Number: 0.271 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.