

## A0270169 Connectivity Accessories - BIX DESIGNATION STRIP



For more Information  
please call

1-800-Belden1

### General Description:

BIX DESIGNATION STRIP

### Usage (Overall)

Suitable Applications:	IBDN System 4800, 3600, 2400, 1200, Telecom Room
Related Parts:	BIX Termination Kit

### Physical Characteristics (Connectivity)

#### Dimensions

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
0.750	6.660	0.180

#### Materials

Materials:

Description	Material
DESIGNATION STRIP	Plastic - UL94V-0

#### Color

Color:	White
--------	-------

#### Weight

Weight:	0.010 lbs.
---------	------------

#### Packaging

Packaging:	50 per packaging in a clear plastic bag.
------------	--

### Mechanical Characteristics (Connectivity)

Storage Temperature Range:	-40°C To +70°C
Installation Temperature Range:	-10°C To +60°C

### Applicable Specifications and Agency Compliance (Overall)

#### Suitability

Suitability - Indoor:	Yes - Indoor
-----------------------	--------------

### Notes (Overall)

#### Product Family

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
A0270169	1 EA	0.013 LB		Q	BIX DESIGNATION STRIP

#### Notes:

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 0    Revision Date: 03-23-2012

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.