



Powering Business Worldwide

pe.eaton.com

Eaton Series C complete molded case circuit breaker

GD3020S1

UPC:786679035412

Dimensions:

- **Height:** 4.88 IN
- **Length:** 2.63 IN
- **Width:** 3 IN

Weight:2.18 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Amperage Rating:** 20A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 14 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 480 Vac, 125/250 Vdc
- **Trip Type:** Fixed thermal, fixed magnetic
- **Circuit Breaker Type:** GD
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** G-frame
- **Series:** Series C
- **Shunt Trip:** 120V three-pole left
- **Frequency Rating:** 50/60 Hz

Supporting documents:

- [UL listed 100%-rated molded case circuit breakers](#)
- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case](#)



Breaker Terminals

- [Motor protection circuit breakers product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Multi-wire lugs product aid](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [StrandAble terminals product aid](#)
- [Eaton's Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Installation Instructions for GD/GWF Molded Case Circuit Breakers and Switches](#)
- [Breaker service centers](#)
- [Eaton Specification Sheet - GD3020S1](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)
- [MOEM MCCB product selection guide](#)

Certifications:

- [UL Listed](#)

Product compliance: No Data