

# Specifications

Photo is representative

## Eaton XTCE032C10B

Eaton XT IEC contactor, 32A, 220 Vac 50 Hz, 240 Vac 60 Hz, 1NO, 32A, Frame C, 45 mm, 50-60 Hz, 3, 5, 5/ 10, 10, 20, 25 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, , Screw terminals, FVNR

### General specifications

<b>PRODUCT NAME</b>	Eaton XT IEC contactor
<b>CATALOG NUMBER</b>	XTCE032C10B
<b>EAN</b>	4015082772598
<b>PRODUCT LENGTH/DEPTH</b>	4 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	3.5 in
<b>PRODUCT WEIGHT</b>	0.5 lb
<b>COMPLIANCES</b>	CE Marked RoHS Compliant
<b>CERTIFICATIONS</b>	UL Listed CSA Certified IEC 60947 EN 60947
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	32A
<b>HP RATING - MAX</b>	3, 5, 5/ 10, 10, 20, 25 hp (1/3PH @115,200,230/200,230,460,575 V)
<b>NUMBER OF POLES</b>	Three-pole
<b>TYPE</b>	Full voltage non-reversing contactor
<b>FREQUENCY RATING</b>	50-60 Hz
<b>FRAME SIZE</b>	45 mm
<b>TERMINALS</b>	Screw terminals
<b>COIL VOLTAGE</b>	220-240 Vac, 50/60 Hz
<b>CONTACT CONFIGURATION</b>	1 NO
<b>CONTINUOUS AMPERE RATING</b>	32 A
<b>SERIES</b>	XT IEC
<b>OPERATION</b>	Non-reversing

## Resources

<b>CATALOGS</b>	<a href="#">Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1</a>
<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - XTCE032C10B</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

