



TE Connectivity: Every Connection Counts
© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved

+ RELAYS, CONTACTORS & SWITCHES



TO-5/.100 GRID



✓ Active

TE CONNECTIVITY (TE)

JMAWDD-26XL=M39016/20-012L

CII

JMAWDD-26XL

TE Internal Number: 5-1617542-3

Mil-Spec: M39016/20-024L

[Not EU RoHS or ELV Compliant](#)

[Find Compliant Alternatives](#)

Contact Arrangement **2 Form C, DPDT, 2 C/O**

Input Voltage (VDC) **26.5**

Coil Suppression Diode **With**

MOSFET Driver **Without**

Transistor Driver **Without**

Catalog Pages/Data Sheets

[5-1773450-5_sec1_MA](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

MOSFET Driver

Without

Enclosure Type

Hermetically Sealed

Product Type

Relay

Relay Type

Military/Aerospace High Performance

Configuration Features

Transistor Driver

Without

Electrical Characteristics

Input Voltage (VDC)

26.5

Coil Suppression Diode

With

Coil Voltage (VDC)

26.5

Coil Resistance (Ω)

1560

Coil Power Rating (DC) (mW)

450

Coil Polarity Protection Diode	With
Actuating System	DC
Vibration	30G's, 10 – 3000Hz
Coil Power Measurement	Milliwatts
Coil Magnetic System	Non-Polarized, Monostable
Shock	75G's, 6ms

Contact Features	Contact Arrangement	2 Form C, DPDT, 2 C/O
	Contact Current Rating (A)	1
	Contact Current Class	Low Level – 1 A

Termination Features	Termination Type	Long Leads
----------------------	------------------	-------------------

Mechanical Attachment	Mounting Type	Printed Circuit Board
-----------------------	---------------	------------------------------

Usage Conditions	Operating Temperature Range (°C)	-65 – 125
------------------	----------------------------------	------------------

Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE
--------------------	---