Straight Blade Devices

50 Ampere, 125, 250 Volts, 277 Volts AC and 125/250 Volts

2 Pole, 3 Wire Grounding and 3 Pole, 3 Wire Non-Grounding

Single Receptacles and Plugs

Fed.Spec.

50A, 125V 2 Pole, 3 Wire Grounding Receptacles and Plugs

IP20 SUITABILITY



50A 125V NEMA 5-50R UL CSA 2 HP



50A 125V NEMA 5-50P UL CSA 2 HP

Description	Cord Diameter	Catalog Numbers	
Receptacle, black RTP.	–	**HBL9360***	–
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	–	**HBL9361**

*Note: *For dimensions, see HBL9308 on page A-37.*



HBL9361

50A, 250V 2 Pole, 3 Wire Grounding Receptacles and Plugs

IP20 SUITABILITY




50A 250V NEMA 6-50R UL CSA 3 HP



50A 250V NEMA 6-50P UL CSA 3 HP

Description	Cord Diameter	Catalog Numbers	
Receptacle, black RTP.	–	**HBL9367**	–
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	–	**HBL9368**



HBL7962

50A, 277V AC 2 Pole, 3 Wire Grounding Receptacles and Plugs

IP20 SUITABILITY




50A 277V AC NEMA 7-50R UL CSA 5 HP



50A 277V AC NEMA 7-50P UL CSA 5 HP

Description	Cord Diameter	Catalog Numbers	
Receptacle, black RTP.	–	**HBL9365**	–
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	–	**HBL9379**



Representative of surface mount receptacle

50A, 125/250V 3 Pole, 3 Wire Non-Grounding Receptacles, Connector Body and Plugs

IP20 SUITABILITY



50A 125/250V NEMA 10-50P UL Listed 3(2) HP



50A 125/250V NEMA 10-50P UL Listed 3(2) HP

Description	Cord Diameter	Catalog Numbers	
Receptacle, black phenolic.	–	**HBL7962**	–
Receptacle, surface mount aluminum housing.	–	**HBL7940**	–
Connector body, Insulgrip, nylon.	.625"-1.218" (15.9-30.9)	**HBL7515C**	–
Plug, Insulgrip, nylon.	.625"-1.218" (15.9-30.9)	–	**HBL7513C**
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	–	**HBL7977**

Note: See page A-46 for accessories.



HBL7515C



HBL7513C