

HBL9368 -- Straight Blade Products, Plug



2-Pole 3-Wire Grounding, 50A 250V, 6-50P, 4-Position Angle, Black and White Nylon

Product Specifications	
Product Type	 Plugs
Body Style	Angle
Standard	NEMA
Amperage	50A
Voltage	250V
Poles and Wires	2 Pole, 3-Wire Grounding
Hospital Grade ?	No
Plug/Connector Grade	Insulgrip
Color	 Black
NEMA No.	6-50P
Horsepower	3
Cord Dia.	.625"-1.187" (15.9-30.2)
Type	3 Pole, 4 Wire, Grounding
Rating	30A, 125/250V
Certification	UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280
IP Suitability	IP20
Housing Material	Supertough® Nylon
Blade Holder Material	Reinforced Thermoplastic Polyester
Retainer Material	Reinforced Thermoplastic Polyester
Cord Clamp Material	Reinforced Thermoplastic Polyester
Contact Blades Material	.060" Brass
Ground Contact Blade Material	.078" Brass (.078")
Terminal Screw Material	Steel - Zn plated
Ground Screw Material	Plated Steel
Box Terminals Material	Brass
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#12-#4 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	Receptacle: UL 94 V0. Plug: UL 94 HB (Housing), UL 94 V0 (Blade Holder and Retainer).
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
UPC Number	783585015286
Weight in LBs	0.550
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

