



NOTES:

1. FOR USE WITH RG-8, 8A, 11, 11A & 213/U CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-7-2.
3. FOR CABLE TRIMMING USE KTJ-124 & KTD-179.
4. FOR CRIMPING USE DIE KTH-1078.
5. MATERIALS:
 INSULATOR: HIGH DENSITY POLYETHYLENE, MIL-P-22748
 GASKETS: SIL. RUB., ZZ-R-765
 K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
 CONTACT: BER. COP., ASTM-B-196
 SPRING: STAINLESS STEEL, TYPE 302
 ALL OTHER PARTS: BRASS, ASTM-B16
6. FINISHES:
 CENTER CONTACT: HARD GOLD PLATE PER MIL-G-45204
 SPRING: PASSIVATE PER QQ-P-35
 ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
7. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: NON-CONSTANT
 VOLTAGE RATING: 20 KVDC
 INSULATION RESISTANCE: 10^6 MEGOHMS
 CURRENT CARRYING CAPACITY: 25 AMPS @ 30°C TEMP RISE

SD1765-1

REVISIONS	
ISSUE	CHANGES
4	CN 34190 C REDRAWN JCA 10/30/92
5	CN 37941 E HVN 11/24/99
6	CN 39710 C DRK 11/22/06
H	REVISED PER ER ER20507 GGR 12/03/2009

CUSTOMER SALES DRAWING

SCALE 2:1
APPROX SURFACE AREA
USED ON

REF:
PLUG, 20 KV

DRAWN JCA	DATE 10/30/92
DESIGN LI	DATE 11/02/92
APPR.	DATE

KINGS
by WINCHESTER

Winchester Electronics
82 Barnes Industrial
Road North
Wallingford, CT 06492

SD1765-1