



23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579-4875 or (310) 534-1505 Fax: (310) 534-1424
E-mail: webmaster@ledtronics.com
Website: <http://www.ledtronics.com>

PC120TG4-140

Green

T1 (3mm) Right-Angle 0.20" Centerline PCB LEDs
45° viewing angle

DWG BY:
BL / GP
09-12-07

CHK BY:
PL
11-29-07

QA:

__-__-__

MFG:

__-__-__

REVISION LTR: -

11-28-07


● **Features:**

1. Chip material: GaP/GaP
2. Emitted color : Green
3. Lens Appearance : Green Diffused
4. Low power consumption.
5. High efficiency.
6. Versatile mounting on P.C. Board or panel.
7. Low current requirement.
8. 3mm diameter package.
9. This product is RoHS compliant.

● **Applications:**

1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

● **Package dimensions**



Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is ±0.25mm (0.01") unless otherwise specified.
3. Lead spacing is measured where the leads emerge from the package.
4. Specifications are subject to change without notice.

● **Absolute Maximum Ratings(Ta=25°C)**

| Parameter | Symbol | Rating | Unit |
|------------------------------------|------------------|-----------------------|------|
| Power Dissipation | P _d | 80 | mW |
| Forward Current | I _F | 30 | mA |
| Peak Forward Current* ¹ | I _{FP} | 150 | mA |
| Reverse Voltage | V _R | 5 | V |
| Operating Temperature | T _{opr} | -40°C~80°C | |
| Storage Temperature | T _{stg} | -40°C~85°C | |
| Soldering Temperature | T _{sol} | 260°C (for 5 seconds) | |

*¹Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

● **Electrical and optical characteristics(Ta=25°C)**

| Parameter | Symbol | Condition | Min. | Typ. | Max. | Unit |
|--------------------------|-------------------|----------------------|------|------|------|-------|
| Forward Voltage | V _F | I _F =20mA | - | 2.2 | 2.6 | V |
| Luminous Intensity | I _v | I _F =20mA | - | 20 | - | mcd |
| Reverse Current | I _R | V _R =5V | - | - | 100 | μA |
| Peak Wave Length | λ _p | I _F =20mA | - | 562 | - | nm |
| Dominant Wave Length | λ _d | I _F =20mA | - | 565 | - | nm |
| Spectral Line Half-width | Δλ | I _F =20mA | - | 27 | - | nm |
| Viewing Angle | 2θ _{1/2} | I _F =20mA | - | 45 | - | deg |
| Radiant Intensity | | I _F =20mA | - | - | - | mW/sr |
| Chromaticity Coordinates | X | I _F =20mA | - | 0.41 | - | |
| | Y | | - | 0.58 | - | |

● **Typical electro-optical characteristics curves**

Fig.1 Relative intensity vs. Wavelength




Fig.2 Forward current derating curve vs. Ambient temperature




Fig.3 Forward current vs. Forward voltage




Fig.4 Relative luminous intensity vs. Ambient temperature




Fig.5 Relative luminous intensity vs. Forward current





Fig.6 Radiation diagram



● **Bin Limits**

1. Intensity Bin Limits (At $I_F=20\text{mA}$)

| Bin Code | Min. (mcd) | Max. (mcd) |
|-----------------|-------------------|-------------------|
| H | 5.5 | 8.2 |
| J | 8.2 | 12.3 |
| K | 12.3 | 18.5 |
| L | 18.5 | 28 |
| M | 28 | 42 |

● Bin : x



NOTES: 1. Tolerance of measurement of luminous intensity. :±15%