

1	2	3	4	5	6	7	8	
				REV.	ECN NO.	DATE	SIGN	DESCRIPTION
				B	LEN-910103~106	2009/01/08	Vicky	Update the drawing.
				C	LEN-0A0046~49	2010/09/03	Zhang Xing	Change Dimension.

Technical drawing of a cable connector assembly. The drawing shows a side view of the assembly. A cable, labeled 'Cable 2', has a diameter of 5.0mm. It is connected to a plug, labeled '1', which has a length of 27.7mm. The plug is inserted into a receptacle, labeled '2', which has a length of 24.0mm. The total length of the assembly is indicated as @L(mm). The drawing also includes a top view of the plug and receptacle, showing four pins. The plug has pins 1, 2, 3, and 4. The receptacle has pins 1, 2, 3, and 4. The drawing is labeled '105-04AFMM-SR7AXX' and '105-04AFMM-SR7000 (1)'. The color is specified as 'Color: Black'.

105-04AFMM-SR7AXX

XX:01~99Meters
01:01Meter
02:02Meters
:
:
99:99Meters

Cable Length(L):01~99Meters

Notes:

- * @ Important Dimension.
- * Waterproof Rate:IP67.
- * Connector:Nylon+GF,Black.
- * Male Pin:Copper Alloy,Gold Plated.
- * Cable:UL2464 24AWG*4C+Talc,Black, PVC Jacket,UV Resistant,OD=5.0mm.
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

Conn.

Pin Assignments

4	Green	綠
3	Yellow	黃
2	Brown	棕
1	White	白
Conn.	Wire Color	

Pin Out

UNIT:mm

TOLERANCE ±0.5 mm

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
DWG NO	CHECKED BY	DATE
CUSTOMER	APPROVED BY	DATE