

9048.0202

Product number

Actuation type	direct
Weight	7.200 g
Switching function	Changeover switch with OFF position in the center (DPDT - Center OFF)
Number of poles	2 - pole
Connections	Solder terminal, sealed
Mechanical life endurance	5E4
Contact system	5E4
Rating IEC	5 A 48 V AC 4 A 30 V DC
Contact resistance (new condition)	< 20 mOhm
Insulation resistance (new condition)	> 1000 MOhm
Voltage strength at 250 V	Function insulation / Basic insulation null V Reinforced insulation null V Small contact distance > 1000 V
Actuators	screw sleeve, silvermetallic, CuZn chrome-plated lever, CuZn chrome-plated
Housing description	base plate: olivegreen bracket plate: stainless steel threaded socket: CnZn nickel-plated, hexagonal nuts of nickel-plated CuZn locking ring: Duroplast (base) / chromated galvanized steel (bracket plate) toothed disc: Duroplast (base) / chromated galvanized steel (bracket plate)

Connection surface	Bearing connection	silver plated
	External connection	silver plated
Contact material	Ag	
Contact type	lifting contact	
Miscellaneous	other screw sleeves 9090.02... In other colours, see additional parts	
Type of fastening	central fastening M6 x 0.75	

All information subject to possible technical changes