

Honeywell Sensing and Control

Search

narrow your search

Products

- Controls Monitoring and Lighting (354)
- Machine Safety (1726)
- Sensors (7074)
- Switches (9814)

Technology

- Control and Instrumentation (1063)
- Electromechanical (9357)
- Microstructure (2328)
- Optical/Infrared (1077)
- Thick Film (1764)
- More...

Need Help?

[Click here to contact us](#)

58C22K Cermet and Wirewound Potentiometers

(Home : Products)



Actual product appearance may vary.

58 Series Industrial Potentiometer, Wire Wound Element, Solder lug Terminals, 4 W Power Rating, 2 kOhm Resistance Value

[Sales & Service](#)

[Distributor Inventory](#)

[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Potentiometer Type	Industrial
Element Type	Wire Wound
Terminal	Solder lug
Power Rating	4 W
Resistance Value	2 kOhm
Resistance Tolerance	±5 %
Linearity	±2 %
Bushing Thread	9,53 mm [0.375 in] x 32 NEF-2A
Bushing Length	12,7 mm [0.5 in]
Bushing Type	Locking
Shaft Diameter	6,35 mm [0.25 in]
Shaft Length	15,88 mm [0.625 in]
Shaft Ending	Slotted
Body	42.93 mm [1.69 in] diameter, ± 0.79 mm [0.031 in], except at terminal standoff
Electrical Taper	Linear
Operating Temperature	-55 °C to 105 °C [-67 °F to 220 °F]
Working Voltage (Max.)	350 V
Rotational Life	25000 cycles
Mechanical Rotation	300°
Availability	Global
Series Name	58
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers