




Home > Products > MICRO SWITCH™ Toggle Switches > TL > Product Page

3TL32-12A



Actual product appearance may vary.

TL Series Toggle Switch, 3 pole, 3 position, Leadwire terminal, Locking Lever

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

Features

Environmentproof sealing
 1,2, and 4 pole circuitry
 Standard and pull-to-unlock levers
 2 and 3 position, maintained and momentary toggle action
 Temperature range: -85° F to +160° F
 Completely sealed switching chamber
 Step-design case provides added space between terminals to help prevent shorting
 UL recognized, CSA certified
 CE approved

Potential Applications

Industrial machinery and equipment
 Military and commercial aviation
 Construction equipment
 Test instruments
 Agricultural machinery
 Process control
 Medical instrumentation

Description

MICRO SWITCH™ TL Series toggle switches have high strength, temperature resistant, non-tracking case material and silver cadmium oxide contacts. Pull-to-Unlock toggle levers prevent accidental operation; the lever must be pulled approx. 2,3 mm (0.09 inches) to change positions.

Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

Product Specifications															
Circuitry/Operating action	<table border="0"> <tr> <th>Keyway Maintained Position</th> <th>Center Maintained Position</th> <th>Opposite Maintained Keyway Position</th> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </table>	Keyway Maintained Position	Center Maintained Position	Opposite Maintained Keyway Position											
Keyway Maintained Position	Center Maintained Position	Opposite Maintained Keyway Position													
Product Type	MICRO SWITCH™ Toggle Switch														
Lever Lock	 Locked in three position														
Ampere/Voltage Range (Resistive Load)	0.5 A to 20 A at 0.5 Vdc to 28 Vdc, 0.75 A at 115 Vdc, 0.5 A to 15 A at 0.5 Vac to 277 Vac, 0.5 A at 250 Vdc														
Circuitry	3PDT														
Action	3 position														
Mounting	Bushing 15/32 in														
Lamp Type	Incandescent														
Termination	Leadwire														
Lever Type	Locking														
UL/CSA Rating Code	L191: 15 A - 125, 250, 277 Vac; 1/2 Hp - 125 Vac; 1 Hp - 250, 277 Vac; 5 A - 120 Vac "L"														
Comment	FAA-PMA approved, special lever construction to incorporate lighted button														
Availability	Global														
UNSPSC Code	30211908														
UNSPSC Commodity	30211908 Toggle switches														
Series Name	TL														

Keyword Search

Search for product and support information.

All Sensing and Contr

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)