



HONEYWELL

SCC15DN

See full Datasheet below...

onlinecomponents.com

THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

BUY NOW



MASTERTM
ELECTRONICS

BUY NOW

masterelectronics.com & onlinecomponents.com
are **authorized** e-commerce distributors
of electronic components.



Home > Products > Piezoresistive Silicon > SCC > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

SCC15DN



Actual product appearance may vary.

Pressure Sensors: Measurement Type: Differential, Gage; 0 psid to 15 psid Operating Pressure, Constant Current, "N" Package - Straight Port

Features

Low Cost Sensor Element
Internal Temperature Compensation
Differential or Gage Pressures

Potential Applications

Pneumatic Controls
Automotive Diagnostics
Medical Equipment
Dental Equipment
Environmental Controls

Description

The SCC Series sensors offer an extremely low cost sensor element with a temperature stable output when driven with a constant current source. These integrated circuit sensors were designed for extremely cost sensitive applications where precise accuracy over a wide temperature range is not required. This series is intended for use with non-corrosive, non-ionic working fluids such as air, and dry gases.

Absolute devices have an internal vacuum reference and an output voltage proportional to applied pressure. The differential devices allow application of pressure to either side of the diaphragm and devices are thereby available to measure both differential and gage pressures.

This product is packaged either in standard low cost chip carrier ? button? package or a DIP package. Both packages are designed for applications where the sensing element is to be integral to the OEM equipment. These packages can be o-ring sealed, epoxied, and/or clamped onto a pressure fitting. A closed bridge four pin SIP configuration is provided for electrical connection to the button package. The DIP package offers a 5-pin open bridge configuration.

Supporting Documentation

[▾ Dimensions](#)

[▾ Electrical Connections](#)

[▾ Equivalent circuit](#)

Product Specifications	
Measurement Type	Differential, Gage
Signal Conditioning	Unamplified
Pressure Range	0 psid to 15 psid
Maximum Overpressure	30 psi
Supply Current	1.5 mA max.
Compensated	Yes
Output Calibration	No
Response Time	0.1 ms typ.
Termination	PCB
Port Style	Straight
Package Style	N
Full Scale Span	55 mV
Zero Pressure Offset	- 30.0 mV min., - 10.0 mV typ., 20.0 mV max.
Accuracy (% Best Fit Straight Line)	.5 %
Input Resistance	4.0 kOhm min., 5.0 kOhm typ., 6.5 kOhm max.
Output Resistance	4.0 kOhm min., 5.0 kOhm typ., 6.5 kOhm max.
Operating Temperature Range	-40 °C to 85 °C [-40 °F to 185 °F]
Compensated Temperature Range	0 °C to 50 °C [32 °F to 122 °F]
Storage Temperature Range	-55 °C to 125 °C [-67 °F to 257 °F]
Media Compatibility	Clean, dry gases only.
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Availability	Global
Series Name	SCC

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)