



# HONEYWELL

## VPR20H3500

*See full Datasheet below...*

**onlinecomponents.com**

THE ONLINE DISTRIBUTOR OF ELECTRONIC COMPONENTS

**BUY NOW**



**MASTER**<sup>TM</sup>  
ELECTRONICS

**BUY NOW**

masterelectronics.com & onlinecomponents.com  
are **authorized** e-commerce distributors  
of electronic components.



Home > Products > Wirewound Resistors > VPR > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## VPR20H3500



Actual product appearance may vary.

**VPR Series, 3.5 kOhms, 20.0 W, Fixed, Wirewound Resistor**

### Features

Rugged vitreous enamel  
 Low cost  
 All-welded construction  
 Solder lead mounting option  
 Meets or exceeds MIL-R-26 standards

### Potential Applications

Power supplies  
 Power dissipation circuits  
 Load adjustors for power amplifiers

### Description

The VPR Series consist of small, highly durable, power resistors. The resistors have uniform windings and conformal vitreous enamel coatings that provide uniform heat dissipation and appearance. The VPR series offer lead or lug connections. They have tinned terminals solderable to MIL-R-26 standards.

**Note:** Not suitable for high frequency applications.

### Supporting Documentation

[Dimensions](#)

Product Specifications	
Resistor Type	Fixed
Power Rating	20 W
Resistance Value	3.5 KOhms
Terminal Type	Lug,Axial
Housing Material	Vitreous enamel
Tolerance	± 5%
Temperature Coefficient	± 100 ppm/ °C
Availability	Global
UNSPSC Code	32121608
UNSPSC Commodity	32121608 Wire Wound Resistor
Series Name	VPR

### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)