

[Home](#)[Products](#)[About us](#)[Contact](#)[Support](#)

**NEUTRIK**[Home](#)[Products](#)[About us](#)[Contact](#)[Support](#)

[Products](#) > [Audio](#) > [XLR](#) > [XLR Chassis Connectors](#) > [B Series](#) > NC3MBH-0
[print](#)

NC3MBH-0

3 pole male XLR receptacle, grounding: ground contact connected to shell ground, but not to front panel and Pin 1, steel retention lug, horizontal PCB mount

Same as A series with exception of a metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC practice. UL recognized component.



Downloads

[Product Guide 2014, 02 XLR](#)
[Drawing NC3MBH-0](#)
[Drawing NC3MBH-0](#)

Links

[UL Certificate \(ECBT2.E135070\)](#)

Features & Benefits

- Smallest XLR receptacles, highest packing density
- Metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC and RF protection
- Housing flammability UL94V-0


Technical Information [▼ hide](#)

Product	
Title	NC3MBH-0
Connection Type	XLR
Gender	male
Electrical	
Capacitance between contacts	≤ 4 pF
Contact resistance	≤ 5 mΩ (inner)
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 GΩ (initial)
Rated current per contact	6 A
Rated voltage	50 V
Grounding Options	ground contact connected to shell ground, but not to front panel and Pin 1
Mechanical	
Insertion force	≤ 20 N
Withdrawal force	≤ 20 N
Lifetime	> 1000 mating cycles
Wiring	Horizontal PCB mount
Locking device	Latch lock
Mounting direction	rear
Chassis shape	B

Mounting	B-Screw
Material	
Ring	Zinc diecast (ZnAl4Cu1)
Flange	Metal
Environmental	
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C

Accessories

B-SCREW-1-8



CAS-DUMMY



SCM



NDM



ACRM-*

