

Shock protection - EMLPR (26,5X26,5) - 0800361

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shock protection, Sheet, transparent, unlabeled, mounting type: adhesive, lettering field size: 26.5 x 26.5 mm, Number of individual labels: 30

Your advantages

- High level of mechanical and chemical stability
- Suitable for permanent outdoor use
- Stuck or snapped onto labeled CARRIER ... to protect the labeling
- Extremely thick, yet flexible and transparent shock protection

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 612517
GTIN	4046356612517
Weight per Piece (excluding packing)	9.400 g
Custom tariff number	39199080
Country of origin	Germany

Technical data

Dimensions

Length (b)	26.5 mm
Width (a)	26.5 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
---------------------------------	------------------

Shock protection - EMLPR (26,5X26,5) - 0800361

Technical data

Ambient conditions

Recommended storage conditions	18-26 °C / 60 % relative humidity.
--------------------------------	------------------------------------

General

Color	transparent
Components	halogen-free
Material	PUR
Number of individual labels	30
Number of individual labels per row	3
Adhesive	Acrylic
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	4000 h
Result of weather resistance test	Test passed
Alternating condensation climate with SO2 test specification	following DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Foil strength	210 µm
Marking mounting type	adhesive

Environmental Product Compliance

	1-Methyl-2-pyrrolidone (NMP) 872-50-4
	2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol (UV-328) 25973-55-1

Classifications

eCl@ss

eCl@ss 10.0.1	27400629
eCl@ss 4.0	24190200
eCl@ss 4.1	24190200
eCl@ss 5.0	27149100
eCl@ss 5.1	27141100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149129
eCl@ss 8.0	27149129
eCl@ss 9.0	27400629

Shock protection - EMLPR (26,5X26,5) - 0800361

Classifications

ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC002848
ETIM 5.0	EC001288
ETIM 6.0	EC001288
ETIM 7.0	EC001288

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504