

Shrink sleeve - WMS 4,8 (30X9)RXL YE - 0803313

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, perforated, Cable diameter: 1.6-4.8 mm, Lettering field: 30 x 9 mm

Why buy this product

- ☒ The sleeves are pre-assembled for optimum use of material
- ☒ WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- ☒ The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- ☒ The shrink sleeves provide additional electrical insulation and mechanical protection for the conductors
- ☒ Up to four markers per sleeve are separated by perforations

RoHS

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	1,460.000 g
Custom tariff number	39173200
Country of origin	China

Technical data

Dimensions

Length (b)	30 mm
Width (a)	9 mm
Cable diameter	1.6 mm ... 4.8 mm

Ambient conditions

Ambient temperature (operation)	-55 °C ... 135 °C
---------------------------------	-------------------

General

Color	yellow
Base element material	polyolefine

Shrink sleeve - WMS 4,8 (30X9)RXL YE - 0803313

Technical data

General

Components	Halogen-free
Material	Polyolefine
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	5000
Number of individual labels per row	2

Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------