

## Conductor marker carrier - PATG 1/23 - 1013847

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 1.5 ... 2.5 mm, lettering field size: 23 x 4 mm

### Your advantages

- The corresponding UC-WMT ..., US-WMT ..., UCT-WMT ... and EMT ... insert labels are used for marking
- These conductor marking systems consist of marker carriers and insert labels
- The PATG ... collar is a captive marker carrier
- Can be used to mark conductors with a diameter of 0.6 ... 50 mm

### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| Minimum order quantity               | 1000 pc   |
| GTIN                                 | <br>4 017918 014032 |
| GTIN                                 | 4017918014032   |
| Weight per Piece (excluding packing) | 0.407 g   |
| Custom tariff number                 | 39269097  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|                |                   |
|----------------|-------------------|
| Length (b)     | 23 mm             |
| Width (a)      | 5 mm              |
| Cable diameter | 1.5 mm ... 2.5 mm |

#### Ambient conditions

# Conductor marker carrier - PATG 1/23 - 1013847

## Technical data

### Ambient conditions

|                                 |                  |
|---------------------------------|------------------|
| Ambient temperature (operation) | -50 °C ... 80 °C |
|---------------------------------|------------------|

### General

|   |                      |
|---|----------------------|
| Color   | transparent          |
| Type  | Profile              |
| Components  | Silicone-free        |
| Flammability rating according to UL 94                              | V0                   |
| Material  | PVC                  |
| RoHS compliant  | Yes                  |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result  | Test passed          |
| Marking mounting type   | slide-on             |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27061700 |
| eCl@ss 4.1 | 27061700 |
| eCl@ss 5.0 | 27400400 |
| eCl@ss 5.1 | 27400400 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149153 |
| eCl@ss 8.0 | 27400401 |
| eCl@ss 9.0 | 27400401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC002248 |
| ETIM 6.0 | EC001530 |
| ETIM 7.0 | EC001530 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |

## Conductor marker carrier - PATG 1/23 - 1013847

### Classifications

#### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 11    | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2  | 39131504 |
| UNSPSC 18.0  | 39131504 |
| UNSPSC 19.0  | 39131504 |
| UNSPSC 20.0  | 39131504 |
| UNSPSC 21.0  | 39131504 |