

Fuse holder - TTC-6-FC-UT/50 - 1104514


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse carrier for surge protective devices of the TERMITRAB complete product range with screw connection technology. Multi-level connection on TTC-6 housings possible. For conventional 5x20 mm miniature fuses.



Key Commercial Data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 055626 971520
GTIN	4055626971520
Weight per Piece (excluding packing)	5.100 g
Custom tariff number	85363010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Height	24 mm
Width	6.2 mm +0.1 mm
Depth	47 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 4000 m (amsl (above mean sea level))
Degree of protection	IP20

General

Housing material	PBT
Flammability rating according to UL 94	V-0
Color	traffic grey A RAL 7042

Fuse holder - TTC-6-FC-UT/50 - 1104514

Technical data

General

Mounting type	Snapping and screwing components onto TERMITRAB complete
---------------	--

Protective circuit

Operating voltage range	60 V DC
Rated current	6.3 A

Connection data


Connection method	Screw connection
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Standards and Regulations

Standards/specifications	EN 60947-7-3 2009
--------------------------	-------------------

Drawings

Dimensional drawing



Fuse holder - TTC-6-FC-UT/50 - 1104514

Classifications

eCl@ss

eCl@ss 8.0	27130890
eCl@ss 9.0	27130890

ETIM

ETIM 5.0	EC002497
ETIM 6.0	EC002497
ETIM 7.0	EC002497