

D-SUB pressure nut - VS-M16 (3-6) - 1688450

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB cap nut with line seal, for sleeve housing VS-09-..., conductor diameter of 3 mm ... 6 mm



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	3.16 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Mechanical characteristics

External cable diameter	3 mm ... 6 mm
Color	gray

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-20 °C ... 80 °C

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Sealing material	Neoprene
Seal material	Neoprene

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

D-SUB pressure nut - VS-M16 (3-6) - 1688450

Classifications

eCl@ss

eCl@ss 4.0	27141209
eCl@ss 4.1	27141209
eCl@ss 5.0	27149109
eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 7.0	27149109
eCl@ss 8.0	27069215

ETIM

ETIM 2.0	EC000441
ETIM 3.0	EC000441
ETIM 4.0	EC000441
ETIM 5.0	EC000814

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

D-SUB pressure nut - VS-M16 (3-6) - 1688450

Drawings

Dimensional
drawing

D-
SUB
cap
nut

Phoenix Contact 2016 © - all rights reserved
<http://www.phoenixcontact.com>