

Wireless module - RAD-80211-XD/HP-BUS - 2900047

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



High power WLAN wireless transceiver (transmitter and receiver) with Ethernet, RS-232, RS-485/RS-422 interface and bus foot for use in I/O extension modules, for 2400 MHz ISM band

Product Features

- ✓ Optional, integrated bus foot for connecting RAD-Line extension modules
- ✓ Provides an interface for data transmission between older serial devices (RS-232, RS-422, and RS-485 interfaces) and an Ethernet network
- ✓ Using the integrated web browser interface, the devices can be configured as an access point, bridge or client
- ✓ Can be used as a Modbus RTU/TCP gateway
- ✓ In bridge mode, up to 40 nodes can be connected to a single network, creating a reliable wireless network
- ✓ Provides an industrial 400 mW wireless transceiver
- ✓ Operates in the license-free 2.4 GHz ISM band
- ✓ Supports TCP/IP, UDP, and IPv4 protocols
- ✓ High level of security with 128/192/256-bit AES encryption according to 802.11i and optional 802.1x authentication can be set
- ✓ Can be programmed for point-to-point, point-to-multipoint, and multipoint-to-point configurations



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	295.0 g
Custom tariff number	85176200
Country of origin	Canada

Technical data

Note

Trade restriction	The products are offered exclusively for export outside the EU and the European Economic Area.
-------------------	--

Dimensions

Width	45 mm
-------	-------

Wireless module - RAD-80211-XD/HP-BUS - 2900047

Technical data

Dimensions

Height	99 mm
Depth	115 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP20

Wireless set

Set contents	1 transceiver
--------------	---------------

Wireless path

Direction	Bi-directional
Frequency range	2.4032 GHz ... 2.4799 GHz
Transmission power	400 mW

Serial interface

Designation	RS-232
Data rate	300 ... 57,6 kBit/s
Connection method	D-SUB 9 (socket)
File format/coding	Asynchronous
Data flow control/protocols	RTS/CTS
Designation	RS-485/RS-422
Data rate	300 ... 57,6 kBit/s
Connection method	COMBICON plug-in screw terminal block

Supply

Supply voltage	24 V DC
Supply voltage range	12 V DC ... 30 V DC
Typical current consumption	230 mA (24 V DC)
Max. current consumption	500 mA (12 V DC)
Nominal power consumption	5.52 W

General

Mounting position	any
Assembly instructions	on standard DIN rail NS 35 in accordance with EN 60715
Housing material	Polyamide PA non-reinforced
Conformance	FCC Directive, Part 15.247
	ISC Directive RSS 210
UL, USA / Canada	Class I, Div. 2, Groups A, B, C, D

Wireless module - RAD-80211-XD/HP-BUS - 2900047

Technical data

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208

ETIM

ETIM 2.0	EC000310
ETIM 3.0	EC000310
ETIM 4.0	EC000310
ETIM 5.0	EC000310

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	43223108
UNSPSC 11	39121008
UNSPSC 12.01	43223108
UNSPSC 13.2	43223108

Drawings

Wireless module - RAD-80211-XD/HP-BUS - 2900047

Block diagram

