

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors



1332630
<https://www.phoenixcontact.com/nl/products/1332630>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



USB PCB connectors, connection direction of the connector to the PCB: 90 °, number of positions: 4, 480 Mbps, Wave soldering, IP20

Your advantages

- Optimized for wave soldering
- Data transmission up to 480 Mbps
- Comfortable tray packing

Commercial data

Item number	1332630
Packing unit	80 pc
Minimum order quantity	80 pc
Sales key	ABNDAA
Product key	ABNDAA
GTIN	4063151630010
Weight per piece (including packing)	2,95 g
Weight per piece (excluding packing)	2,95 g
Customs tariff number	85366930
Country of origin	CN

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors



1332630

<https://www.phoenixcontact.com/nl/products/1332630>

Technical data

Product properties

Orientation to PCB	90.00 °
Number of positions	4
Transmission speed	480 Mbps

Electrical properties

Rated voltage	30 V
Rated surge voltage	1.5 kV
Rated current	1.5 A
Insulation resistance	1000 MΩ

Dimensions

Length	14.5 mm
Width	14.5 mm
Height	7 mm

Material specifications

Material Contact carrier	PA 4T
Flame resistance	UL 94 V0
Halogen-free	yes
Material Housing	Metal
Material Contact	Copper alloy

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 1500
Insertion force	35 N
Withdrawal force	< 10 N

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
Degree of protection (plugged in)	IP20
Degree of protection (Not plugged in)	IP20

Test specification for vibration - sine

Acceleration	5,4g rms
Sweep speed	1 octave/min

Mounting

Processing notes

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors



1332630

<https://www.phoenixcontact.com/nl/products/1332630>

Mounting type	Wave soldering
---------------	----------------

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors




1332630

<https://www.phoenixcontact.com/nl/products/1332630>

Drawings

Diagram



Classification wave soldering profile

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors



1332630

<https://www.phoenixcontact.com/nl/products/1332630>

Classifications

ECLASS

ECLASS-13.0	27460201
ECLASS-15.0	27460201

ETIM

ETIM 10.0	EC002637
-----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CUC-USB2.0-J1ST-AV/UAF-THT - USB PCB connectors



1332630

<https://www.phoenixcontact.com/nl/products/1332630>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2026 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT B.V.
Hengelder 56 6902 PA Zevenaar
Postbus 246 6900 AE Zevenaar
(0316) 59 17 20
sales@phoenixcontact.nl