

Technical drawing of a probe with dimensions in inches and millimeters:

- Top view dimensions:
 - Overall length: $E \pm 1.50$ (38.1 mm)
 - Tip diameter: $A \pm .008$ (.20 mm)
 - Shaft diameter: $D \pm .015$ (.38 mm)
 - Shoulder diameter: $C \pm .015$ (.38 mm)
- Bottom view dimensions:
 - Tip diameter: $B \pm .008$ (.20 mm)

PANDUIT PART NO.	DESCRIPTION	BUNDLE DIA.		A in. (mm)	B in. (mm)	C in. (mm)	D in. (mm)	E in. (mm)	MINIMUM LOOP TENSILE 2"/MIN. lbs. (N)	WEIGHT PER TIE OUNCES (g)
		MIN. in. (mm)	MAX. in. (mm)							
DT14EH-LO	48 IN. LONG TIE	.020 (.51)	14.0 (355)	.500 (12.70)	.059 (1.50)	.490 (12.45)	.718 (18.24)	48.0 (1219)	250 (1112)	1.2 (33)
DT15EH-LO	53 IN. LONG TIE	.020 (.51)	15.0 (381)	.500 (12.70)	.059 (1.50)	.490 (12.45)	.718 (18.24)	53.0 (1346)	250 (1112)	1.3 (36)

DURA-TY CABLE TIES MEET OR EXCEED THE REQUIREMENTS OF TR-TSY-000789, TELCORDIA TECHNOLOGIES.

										DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS		
										PANDUIT CORP. TINLEY PARK, ILLINOIS DURA-TY EXTRUDED CABLE TIES (EXTRA HEAVY)		
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± ANGLES ±		
										UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.		
										DRAWN BY FAB	MAT'L: STRAP & HEAD - BLACK ACETAL EACH HEAD HAS TWO, TYPE 302 STAINLESS STEEL BARBS	
1	8/31/07	JABO		REVISED METRIC DIM 'A' & 'C'	SS-27518	1				DATE 3/16/00		
REV	DATE	BY	CHK	DESCRIPTION	ECN	-	R	CUST	SUP	CHK'D DWW	DRAWING NO. SS-27518	DWG A SIZE