

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Catalog Cut Sheet
 - PDFLAM2SA300-56 ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'LAM2LB600-12-3'

Your search criteria matched only one product, shown below


LAM2LB60012-3



For Use with Stranded Aluminum or Copper Code Conductors

- Dual barrel provides termination of two conductors
- Made from high strength, extruded aluminum alloy to provide premium electrical and mechanical performance
- Tin-plated to inhibit corrosion
- Wide wire range -taking capability minimizes inventory requirements
- Inspection window to visually assure full conductor insertion
- Plated steel or aluminum set screw provides high strength, durable electrical contact between conductor and connector
- LAM2LB connector provided with dual set screws for premium clamping of conductor to connector for heavy duty applications
- UL Listed for use up to 600 V and temperature rated 90°C
- Available with NEMA hole sizes and spacing

Note: These code conductor mechanical lugs are manufactured for use with AWG wire only.

Part Number	LAM2LB600-12-3
Part Description	Aluminum, two-barrel, two-hole tongue connector, type LAM2LB.
Height (In.)	1.50
Height (mm)	38.1
Length (In.)	5.50
Length (mm)	139.7
Stud Hole Size (In.)	1/2
Stud Hole Spacing (In.)	1.75
Tongue Width (In.)	2.85
Aluminum or Copper Conductor Size Range	#2 AWG – 600 kcmil
CE Compliant	No
Conductor Size Range (mm ²)	25 – 300
Figure No.	2
Hex Key Size (In.)	3/8
Pricing Description	Aluminum Mechanical Lug, 2 Hole, 2 Barrel, #2 AWG 600 kcmil, 1/2" (12.7mm) Stud
Tongue Length	3.25
Tongue Length (mm)	82.6
Tongue Thickness	0.38
Tongue Width (mm)	72.4
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.