

Search Results

Evaluate

- FAQ's
- Selection Guides
- PDFPAN-LUG Alum ..

Design a Solution

- Part Drawings
- PDFSplit Bolt, ..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'SBCT250-Q'


Your search criteria matched only one product, shown below

SBCT250-Q



For Specified Combinations of Copper and Aluminum Code Conductors

- Made from high strength copper alloy to provide premium electrical and mechanical performance
- Tin-plated to inhibit corrosion and oxidation
- Offered with dual rating for use with aluminum or copper conductors
- Wide wire range -taking capability minimizes inventory requirements
- Nut hex provides correct fit with socket, box, or open end wrenches resulting in proper torquing of electrical connection
- Free floating pressure bar separates conductors of dissimilar materials for secure connection on a full range of conductor combinations
- UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90°C

Part Number	SBCT250Q
RoHS Compliancy Status	Compliant
Part Description	Copper split bolt connector, tin plated, type SBCT.
Product Type	Mechanical Connectors- Split Bolt
CSA Certified	Yes - Copper Only
UL Listed	Yes - Copper Only
Length (In.)	2.22
Length (mm)	56.4
Min. Tap with One Max. Run	#8 STR
Range of Equal Run & Tap Min.	#1 STR
Range of Equal Run and Tap Max.	250 kcmil
Body Hex	1.03
Nut Hex	1.36
Pricing Description	Split Bolt, Copper, Tin Plated, #1 STR250 kcmil
Tightening Torque (InLbs)	650
Wire Range (mm ²)	25 – 150
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.