

Search Results

Evaluate

- FAQ's
- Performance Data
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- Technology Briefs
- PDFMarine Coppe..
- Videos
- WMV-TX7000 Shiel..

Design a Solution

- Specification Sheets
- PDFTX7000 Shiel..

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- Installation Instructions
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Marin..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..
- PDFTX7000 Shiel..

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'PSM7004BU-KEM'

Your search criteria matched only one product, shown below

PSM7004BU-KEM




- Exceeds requirements of ISO 11801 Class E_A and ANSI/TIA-568-C.2 Category 6A channel standards
- Meets or exceeds the requirements of IEC 61156 -5 Category 7 component standards at swept frequencies up to 600 MHz
- Meets requirements of IEEE 802.3af and IEEE 802.3at for PoE applications
- Robust cable jacket oil and fuel resistant for harsh environments
- Flame rated to meet IEC 60754 -1, IEC 60754-2, IEC 61034-2, IEC 60332-3-24
- Chemical resistance tested to mineral oil IRM 902 (IEC 60811 -2-1) and diesel fuel IRM 903 (IEC 60811-2-1)
- Third party tested to exceed the application requirements of Det Norske Veritas, American Bureau of Shipping, and ETL
- DNV certification number E -10447
- ABS certification number 10 -HS638424 -1-PDA
- Ideal for harsh environments encountered in marine applications, including ship and

offshore/onshore units

- Cable diameter 8.2 mm (0.322 in) nominal
- Installation temperature range: -15°C to 50°C (5°F to 122°F)
- Operating temperature range: -40°C to 85°C (-40°F to 185°F)
- Descending cable length markings enable easy identification of remaining cable which reduces installation time and cable scrap
- Packaged on a reel

Contact customer service for region availability

Part Number	PSM7004BUKEM
RoHS Compliancy Status	Compliant
Part Description	Category 7 low smoke, halogen free, fire retardant (LSHF _{FR}), 4-pair S/FTP shielded marine copper cable. Stranded copper conductors are 4 x 2/0.27mm ² . Conductors are twisted in pairs, each individual twisted pair is surrounded by a foil, covered with an overall braided shield and is protected by an oil and fuel resistant, low smoke, halogen free, and fire retardant jacket.
Product Type	Copper Cable
Color	Blue
Cable Color	Blue
Cable Type	S/FTP
CE Compliant	No
Flammability Rating	LSHF _{FR}
Performance Level	Category 7/Class F
Pricing Description	Copper Cable, Category 7, 4Pair, 23 AWG stranded, S/FTP, LSHF0H SHF1, Blue, Euro Pall 1000m reel
Min. Order UOM	RL
Min. Order Qty.	4
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.