

# HSK-K-Ex-Active Metric 1.292.2001.50

Standard liquid tight strain relief fittings made of fiber reinforced Polyamide

<b> cable diameter </b>	6 – 12 mm
<b> colour </b>	black
<b> Ex-protection level </b>	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
<b> Height </b>	27 mm
<b> Male thread </b>	M 20 x 1,5
<b> Material </b>	Polyamide, fiber reinforced
<b> O-Ring </b>	Buna-N
<b> Operating-Temperature </b>	-20 – 85 °C
<b> Protection category </b>	IP 68 – 10 bar within the specific clamping range
<b> Seal </b>	Buna-N
<b> Thread Length </b>	9 mm
<b> Wrench size </b>	24 mm

// O-Ring FKM and VMQ upon request

### Additional information

- // [Application report](#)
- // [HSK-K-EX-Active \(english\)](#)

**DOWNLOAD 3D DATA**

**Certificates**

**ATEX** **ATEX**

**ADD TO WATCHLIST**

**PRINT**

**SUPPORT**

#### ELECTRIC COMPONENTS

- Circular Connectors
- Industrial Cable Glands
- Industrial Ex Cable Glands
- "Hazardous Areas" Cable Glands
- Conduit Systems
- Customized Projects

#### HEATING EQUIPMENT

- Problem Fixer
- Fittings
- Designtechnic
- Accessories, Spare Parts, Tools

#### INFORMATION

- News
- Imprint
- Privacy Policy
- GTC

#### NEWSLETTER

**SUBSCRIBE TO NEWSLETTER**

This website uses cookies to ensure you get the best experience on our website.

OK