



Flexible Conduits & Fittings

T&B Catalog Number:

VAMLG-36S.30

UPC Number:

78620997669

Status:

Active

Description:

Coarse profile medium wall flexible gray conduit. (VAML) Material - polyamide 6, conduit size NW - 36.

Application

Rail/Infrastructure

Rail/Infrastructure

In passenger areas of railway vehicles

Public buildings to include hospitals, hotels, airports, train and subway stations and shopping centers

Characteristics

Good resistance to ultra violet rays and weathering

Good impact strength

Outstanding self-extinguishing characteristics

Minimal development of smoke and gases

Free from halogen and cadmium

General

Material Polyamide 6

Material-Conduit Core Non-Metallic

Color Gray

System PMAFLEX

Compatible With PMAFIX Pro, PMAFIX, PMA Smart Line, PMAGRIP

Dimension Information

Conduit Size (inches) 1 1/4

Conduit Size NW (mm) 36

Conduit Size Metric (mm) 40

Outside Diameter (inches) 1.67

Inside Diameter (mm) 36

Outside Diameter (mm) 42.5

Static Radius (mm) 65

Rec. Fitting Thread-Metric M40 x 1.5

Rec. Fitting Thread-PG 36

Technical Information

Temperature Range-Continuous (Celsius) -40 to +105

Temperature-Short-Term (Celsius) 160

Fatigue Life Medium

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Packaging

T&B Order Multiple 1

T&B Inner Pack 1

Package in Units 6

T&B Sold in UOM Each

T&B Weight Per UOM 0.44 lbs. Each

Application Support

PMA Reference Guide Available on Website

PMA Conduit Guide	Available on Website
Product Overview-PMAFLEX Conduits	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com