



Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

5356-HT

UPC Number:

78621091060

Status:

Active

Description:

1-1/2 in. 90 degree steel insulated liquidtight high temperature connector.

Features

Sure-Tight gland deflects water away from connector and prevents "pooling" of moisture.

Double beveled sealing ring designed with 5 unique sealing mechanisms and cannot be installed backwards

Safe Edge ground cone provides superior bonding, stronger pullout, easy threading and conductor protection.

Double plating for superior corrosion protection

Heat Curled Insulator molded inside body provides excellent wire protection and easier glide of conductors through and into the fitting.

General

Style	Insulated
Trade Size (inches)	1 1/2
Material	Steel
Finish	Zinc Plating/Clear Chromate

Dimension Information

Dimension A (inches)	2 11/16
Dimension B (inches)	2 15/16
Dimension C (inches)	13/16

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	2
Package in Units	10
T&B Sold in UOM	Each
T&B Weight Per UOM	174 lbs. per 100

Application Support

304 Stainless Steel Corrosion Compatibility Chart - Available on Website

T&B Sales Drawings [wsd-000018](#)

T&B Instruction Sheets [ta02544-tb2](#)

Product Brochure [Available on Website](#)

Certifications



File Nbr:

E 23018

For further technical assistance, please contact us...

8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com