



Flexible Conduits & Fittings

T&B Catalog Number:

BVIVG-U292

UPC Number:

78620995063

Status:

Active

Description:

PMAFIX black female thread adapter with UNEF threads and O-ring. Material - polyamide 6, thread size - 1-3/16 in. -18, conduit size NW - 12.

Application

For use in machine, vehicle and traction building

Characteristics

Very high impact resistance

Vibration proof connection to PMAFLEX conduits

High conduit pull-out strength

Very good chemical properties

Self-extinguishing, free from halogens and cadmium

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6

Color Black

Thread Type UNEF

Compatible With PMAFLEX, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW) 12

Fits to Conduit Size (metric) 16

Fits to Conduit Size (inches) 3/8

Thread Length (mm) 9.0

Thread Size (UNEF) 1 3/16" - 18

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP68 stat. / IP67 dyn.

Packaging

T&B Inner Pack 50

Package in Units 300

T&B Sold in UOM Each

T&B Weight Per UOM 0.15 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

PMAFIX Connectors-Safety and Sealing Systems Available on Website

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com