


C3216C0G2A103J115AA (TDK item description : C3216C0G2A103JT****)

Applications	 Commercial Grade
	 Please refer to Part No. CGA5H2C0G2A103J115AA for automotive use.
Feature	 Mid Voltage (100 to 630V)
Series	C3216 [EIA CC1206]




Size	
Length(L)	3.20mm +/-0.20mm
Width(W)	1.60mm +/-0.20mm
Thickness(T)	1.15mm +/-0.15mm
Terminal Width(B)	0.20mm Min.
Terminal Spacing(G)	1.00mm Min.
Recommended Land Pattern(PA)	2.10 to 2.50mm (Flow Soldering) 2.00 to 2.40mm (Reflow Soldering)
Recommended Land Pattern(PB)	1.10 to 1.30mm (Flow Soldering) 1.00 to 1.20mm (Reflow Soldering)
Recommended Land Pattern(PC)	1.00 to 1.30mm (Flow Soldering) 1.10 to 1.60mm (Reflow Soldering)
Recommended Slit Pattern(SD)	

Electrical Characteristics	
Capacitance	10nF +/-5%
Rated Voltage	100Vdc
Temperature Characteristic	C0G(0+/-30ppm/degC)
Q	1000 Min.
Insulation Resistance	10000MΩ Min.


Other	
Soldering Method	Reflow, Flow
AEC Q200	No
Packing	Blister (Plastic)Taping [180mm Reel]
Package Quantity	2000Pcs Min.

C3216C0G2A103J115AA


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)



C3216C0G2A103J115AA




C3216C0G2A103J115AA



C3216C0G2A103J115AA



C3216C0G2A103J115AA



C3216C0G2A103J115AA(DC Bias = 0V) C3216C0G2A103J115AA(DC Bias = 50V)

