

FP BOX ON/OFF**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The FieldPower® power distributors support error-free installation in an extremely short space of time. Branches and functions integrated in the cover can simply be plugged in. Robust with high protection degree. For cable seals consult accessories

General ordering data

Type	FP BOX ON/OFF
Order No.	1003260000
GTIN (EAN)	4032248698967
Qty.	1 pc(s).

Creation date August 18, 2020 8:10:11 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

FP BOX ON/OFF

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Width	104 mm	Width (inches)	4.094 inch
Height	181 mm	Height (inches)	7.126 inch
Depth	164 mm	Depth (inches)	6.457 inch
Net weight	901.69 g		

Temperatures

Operating temperature, max.	45 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...45 °C	Storage temperature	-40 °C...80 °C
Temperature range, installation, min.	10 °C	Temperature range, installation, max.	40 °C

Clamping capacity, PUSH IN connection, distribution

Blade size	0.6 x 3.5 mm	Blade size, PUSH IN connection	0.6 x 3.5 mm
Cross-section for connected wire PUSH IN connection, solid, min.	0.5 mm ²	Cross-section for connected wire, PUSH IN connection, solid, max.	6 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	6 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	6 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	6 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	6 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²
Cross-section for connected wire, flexible, PUSH IN connection, max.	10 mm ²	Cross-section for connected wire, flexible, PUSH IN connection, min.	0.5 mm ²
Finely-stranded flexible, max. PUSH IN connection	6 mm ²	Finely-stranded flexible, min. PUSH IN connection	0.5 mm ²
Stripping length, PUSH IN connection	14 mm	Wire connection cross section, stranded, PUSH IN connection, max.	6 mm ²
Wire connection cross section, stranded, PUSH IN connection, min.	0.5 mm ²		

IDC connection clamping capacity, power cable

Blade size	0.6 x 3.5 mm	Connection cross-section, finely stranded, max.	6 mm ²
Connection cross-section, finely stranded, min.	2.5 mm ²	Connection cross-section, stranded, max.	6 mm ²
Connection cross-section, stranded, min.	2.5 mm ²	Wire connection cross section, finely stranded, max.	6 mm ²
Wire connection cross-section, finely stranded, min.	2.5 mm ²	Wire cross-section, solid, max.	6 mm ²
Wire cross-section, solid, min.	1.5 mm ²		

General information #96 connectors

Can be coded	Yes, Coded on PE	UL 94 flammability rating	5VA
--------------	------------------	---------------------------	-----

Creation date August 18, 2020 8:10:11 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

2

FP BOX ON/OFF

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

General data

Can be coded	Yes, Coded on PE	Material colour	black
Protection degree	IP65	Silicone	No
Insulating material	Polycarbonate, GF 10	Halogen	No
UL 94 flammability rating	5VA		

Dimensions of box

Height	181 mm	Width	104 mm
--------	--------	-------	--------

Rated data acc. to IEC

Rated cross-section	6 mm ²	Rated current	41 A
Rated impulse withstand voltage	8 kV	Rated voltage	800 V
Standards	UL 508, IEC 60947-7-1		

Rated data acc. to UL

Rated current (Use group D / UL 1059)	16 A	Rated voltage (Use group D / UL 1059)	600 V
Standards	UL 508, IEC 60947-7-1	Wire connection cross section AWG, max.	AWG 8
Wire connection cross section AWG, min.	AWG 18		

Technical data Switch

Clamping range, plug, max.	10 mm ²	Clamping range, plug, min.	0.75 mm ²
Operating voltage	440 V	Plug standards	IEC 60947-3
Pollution severity	3	Power rating AC-23A	7.5 kW
Rated current AC-23A	16 A	Rated short-term current resistance I _{CW}	500 A rms for 1 Second
Switch type	ABB OT16ET3	Terminals - torque	0.8 Nm
Wire connection cross section AWG, max.	AWG 8	Wire connection cross section AWG, min.	AWG 18
auxiliary contact	ABB OA1G10		

Classifications

ETIM 6.0	EC000214	ETIM 7.0	EC000214
eClass 9.0	27-14-24-09	eClass 9.1	27-14-24-09
eClass 10.0	27-14-24-09	UNSPSC	30-21-18-01

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity

[FieldPower](#)

Engineering Data

[WSCAD](#)

Creation date August 18, 2020 8:10:11 AM CEST

Catalogue status 14.08.2020 / We reserve the right to make technical changes.

