

SKMU PG9-K GR**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Similar to illustration

In addition to cable glands for a wide range of applications, the product portfolio is rounded off by plugs, pressure compensation elements, adaptors and the corresponding accessories such as locknuts, sealing rings, flat washers and earthing rings.

General ordering data

Version	SKMU PA (plastic locknut), Locknut, PG 9, 5 mm, Polyamid 6 (PA6 - GF30)
Order No.	1697450000
Type	SKMU PG9-K GR
GTIN (EAN)	4008190880569
Qty.	100 pc(s).

SKMU PG9-K GR

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 1.59 g

Temperatures

Operating temperature -40 °C...100 °C

Operating temperature, max. 100 °C

Operating temperature, min. -40 °C

General information

AF size 1 22 mm

External thread PG 9

Internal thread PG 9

Material Polyamid 6 (PA6 - GF30)

Operating temperature range, max. 100 °C

Pitch of thread 1.41 mm

Thickness 5 mm

Cable glands PG 9

Halogen No

Length of thread 5 mm

O.D. 25.41 mm

Operating temperature range, min. -40 °C

Silicone No

UL 94 flammability rating HB

Classifications

ETIM 6.0 EC000940

ETIM 8.0 EC000940

ECLASS 9.1 27-14-44-24

ECLASS 11.0 27-14-44-24

ETIM 7.0 EC000940

ECLASS 9.0 27-14-44-24

ECLASS 10.0 27-14-44-24

ECLASS 12.0 27-14-08-07

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data [CAD data – STEP](#)Engineering Data [WSCAD](#)Catalogues [Catalogues in PDF-format](#)

Brochures

Data sheet

SKMU PG9-K GR

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Drawings

