

**Cable glands
VG M20-EXE MS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Brass cable glands for use in ATEX areas

General ordering data

Order No.	1737220000
Type	VG M20-EXE MS
Version	Cable gland, Brass, nickel-plated, External thread: M 20
GTIN (EAN)	4008190956691
Qty.	50 pc(s).

**Cable glands
VG M20-EXE MS**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	20 mm	Net weight	8.44 g
--------	-------	------------	--------

Approvals

Approval for cable gland	Ex e II, II 2 GD
--------------------------	------------------

General information

AF size 1	24 mm	Cable gland	metric
Clamping range, max.	13 mm	Clamping range, min.	8.5 mm
External thread	M 20	Length of thread	8 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pitch of thread	1.5	Protection degree with GWDR	IP 68 - 5 bar (30 min.)
Seal insert	CR	Sealing	NBR
Torque for cap nut, max.	27.5 Nm	Torque for cap nut, min.	27.5 Nm
Torque for connecting adapter, max.	6 Nm	Torque for connecting adapter, min.	6 Nm

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-11
eClass 5.1	27-14-91-11	eClass 6.2	27-14-91-11
eClass 7.1	27-14-91-11		

Approvals

Approvals



ROHS	Conform
------	---------