


**cable lug, terminal end
LIR 1,5M3,5 V**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Insulated ring-cable connector made from PVC

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Type	LIR 1,5M3,5 V
Order No.	9200080000
Version	cable lug, terminal end, Insulated cable connector, 0.5 mm ² - 1.5 mm ²
GTIN (EAN)	4032248409846
Qty.	100 pc(s).

**cable lug, terminal end
LIR 1,5M3,5 V**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	20.4 mm	Width (inches)	0.803 inch
Depth	5.8 mm	Depth (inches)	0.228 inch
Net weight	0.4 g		

Connectors

Conductor cross-section, max.	1.5 mm ²	Conductor cross-section, min.	0.5 mm ²
Connection density (S1)	0.75 mm	Connection length (l)	16.05 mm
Dimension	M 3.5	Dimension (bolt)	M 3.5
Identification colour	red	Inside diameter (d1)	3.7 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	5.5 mm	Plastic collar diameter (D)	4 mm
Plastic collar length (b)	11.3 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
eClass 9.0	27-40-02-92	eClass 9.1	27-40-02-12
eClass 10.0	27-40-02-92	UNSPSC	23-17-16-04

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 6 TOOLS 15/16 EN
Engineering Data	EPLAN